



Windows PowerShell Get-Help on Cmdlet 'Import-AzWebAppKeyVaultCertificate'

PS:\>Get-HELP Import-AzWebAppKeyVaultCertificate -Full

NAME

Import-AzWebAppKeyVaultCertificate

SYNOPSIS

Import an SSL certificate to a web app from Key Vault.

SYNTAX

```
Import-AzWebAppKeyVaultCertificate [-KeyVaultName] <System.String> [-CertName] <System.String>
[-ResourceGroupName] <System.String> [-WebAppName] <System.String>
[-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Slot
<System.String>] [-Confirm] [-WhatIf]
[<CommonParameters>]
```

DESCRIPTION

The Import-AzWebAppKeyVaultCertificate cmdlet imports an SSL certificate to a web app from Key Vault.

-CertName <System.String>

KeyVaultCertName of the certificate created in keyvault

Required? true

Position? 1

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-KeyVaultName <System.String>

The name of the keyvault or Id of the KeyVault.

Required? true

Position? 0

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceGroupName <System.String>

The name of the webapp resource group.

Required? true

Position? 2

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Slot <System.String>

The name of the webapp slot.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-WebAppName <System.String>

The name of the webapp.

Required? true

Position? 3

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

None

OUTPUTS

Microsoft.Azure.Commands.WebApps.Models.WebApp.PSCertificate

NOTES

----- Example 1 -----

```
Import-AzWebAppKeyVaultCertificate -ResourceGroupName "Default-Web-WestUS" -WebAppName "ContosoWebApp" `
-KeyVaultName "ContosoKeyVault" -CertName "ContosoCertname"
```

This command imports an SSL certificate to a web app from Key Vault.

----- Example 2 -----

```
Import-AzWebAppKeyVaultCertificate -ResourceGroupName "Default-Web-WestUS" -WebAppName "ContosoWebApp" `
-KeyVaultName '/subscriptions/[sub id]/resourceGroups/[rg]/providers/Microsoft.KeyVault/vaults/[vault name]' `
-CertName "ContosoCertname"
```

This command Import an SSL certificate to a web app from Key Vault using resource id (typically if Key Vault is in another subscription).

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.websites/import-AzWebAppKeyVaultCertificate>