



Windows PowerShell Get-Help on Cmdlet 'Invoke-AzDataFactoryV2TriggerRun'

PS:\>Get-HELP Invoke-AzDataFactoryV2TriggerRun -Full

NAME

Invoke-AzDataFactoryV2TriggerRun

SYNOPSIS

Invokes another instance of a trigger run.

SYNTAX

```
Invoke-AzDataFactoryV2TriggerRun [-DataFactory]
<Microsoft.Azure.Commands.DataFactoryV2.Models.PSDataFactory> [-TriggerName] <System.String> [-TriggerRunId]
<System.String> [-DefaultProfile]
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer> [-PassThru] [-Confirm]
[-WhatIf]
[<CommonParameters>]
```

```
Invoke-AzDataFactoryV2TriggerRun [-ResourceGroupName] <System.String> [-DataFactoryName] <System.String>
[-TriggerName] <System.String> [-TriggerRunId]
<System.String> [-DefaultProfile]
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer> [-PassThru] [-Confirm]
[-WhatIf]
```

[<CommonParameters>]

Invoke-AzDataFactoryV2TriggerRun [-InputObject] <Microsoft.Azure.Commands.DataFactoryV2.Models.PSTriggerRun>
[-DefaultProfile
 <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-PassThru]
[-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Invoke-AzDataFactoryV2TriggerRun command starts another instance of a trigger run with a new trigger run id.

PARAMETERS

-DataFactory <Microsoft.Azure.Commands.DataFactoryV2.Models.PSDataFactory>

The data factory object.

Required?	true
Position?	0
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

-DataFactoryName <System.String>

The data factory name.

Required?	true
Position?	1
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.DataFactoryV2.Models.PSTriggerRun>

The information about the trigger run.

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-PassThru <System.Management.Automation.SwitchParameter>

If specified the cmdlet write true in case operation succeeds.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-ResourceGroupName <System.String>

The resource group name.

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-TriggerName <System.String>

The trigger name.

Required? true

Position? 2

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-TriggerRunId <System.String>

The Run ID of the trigger.

Required? true

Position? 3

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.DataFactoryV2.Models.PSTriggerRun

System.String

Microsoft.Azure.Commands.DataFactoryV2.Models.PSDataFactory

OUTPUTS

Microsoft.Azure.Commands.DataFactoryV2.Models.PSPipeline

NOTES

----- Example 1 -----

```
Invoke-AzDataFactoryV2TriggerRun -ResourceGroupName "ADF" -DataFactoryName "WikiADF" -TriggerName  
"testTumblingWindowTrigger" -TriggerRunId  
08586002468005888497807248799CU16
```

Starts another instance of a trigger run with a new trigger run id, keeping the same windowStartTime and windowEndTime as the original trigger run.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.datafactory/invoke-azdatafactoryv2triggerrun>