



Windows PowerShell Get-Help on Cmdlet 'Invoke-AzDevCenterUserDelayEnvironmentAction'

PS: \> Get-HELP Invoke-AzDevCenterUserDelayEnvironmentAction -Full

WARNING: The names of some imported commands from the module 'Az.DevCenterdata.custom' include unapproved verbs that might make them less discoverable. To find the commands with unapproved verbs, run the Import-Module command again with the Verbose parameter. For a list of approved verbs, type Get-Verb.

NAME

Invoke-AzDevCenterUserDelayEnvironmentAction

SYNOPSIS

Delays the occurrence of an action.

SYNTAX

```
Invoke-AzDevCenterUserDelayEnvironmentAction -Endpoint <String> -Name <String> -EnvironmentName <String>
-ProjectName <String> [-UserId <String>] -DelayTime
    <TimeSpan> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
    <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Invoke-AzDevCenterUserDelayEnvironmentAction -DevCenterName <String> -Name <String> -EnvironmentName
<String> -ProjectName <String> [-UserId <String>] -DelayTime
```

<TimeSpan> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Delays the occurrence of an action.

PARAMETERS

-Endpoint <String>

The DevCenter-specific URI to operate on.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DevCenterName <String>

The DevCenter upon which to execute operations.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of an action that will take place on an Environment.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-EnvironmentName <String>

The name of the environment.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProjectName <String>

The DevCenter Project upon which to execute operations.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-UserId <String>

The AAD object id of the user.

If value is 'me', the identity is taken from the authentication context.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DelayTime <TimeSpan>

The delayed timespan from the scheduled action time.

Format HH:MM.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.DevCenterdata.Models.IDevCenterdataIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.DevCenterdata.Models.Api20231001Preview.IEnvironmentAction

----- EXAMPLE 1 -----

```
PS          C:\>Invoke-AzDevCenterUserDelayEnvironmentAction          -Endpoint  
"https://8a40af38-3b4c-4672-a6a4-5e964b1870ed-contosodevcenter.centralus.devcenter.azure.com/"  
-EnvironmentName myEnvironment -ProjectName DevProject -Name "myEnvironment-Delete" -DelayTime "00:30"
```

----- EXAMPLE 2 -----

```
PS  C:\>Invoke-AzDevCenterUserDelayEnvironmentAction  -DevCenterName  Contoso  -EnvironmentName  
myEnvironment -UserId "me" -ProjectName DevProject -Name  
"myEnvironment-Delete" -DelayTime "05:15"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.devcenter/invoke-azdevcenteruserdelayenvironmentaction>