



Windows PowerShell Get-Help on Cmdlet 'Invoke-AzKustoInviteDatabaseFollower'

PS:\>Get-HELP Invoke-AzKustoInviteDatabaseFollower -Full

NAME

Invoke-AzKustoInviteDatabaseFollower

SYNOPSIS

Generates an invitation token that allows attaching a follower database to this database.

SYNTAX

Invoke-AzKustoInviteDatabaseFollower -ClusterName <String> -DatabaseName <String> -ResourceGroupName <String> [-SubscriptionId <String>] -InviteeEmail <String>

[-TableLevelSharingPropertyExternalTablesToExclude <String[]>] [-TableLevelSharingPropertyExternalTablesToInclude <String[]>]

[-TableLevelSharingPropertyFunctionsToExclude <String[]>] [-TableLevelSharingPropertyFunctionsToInclude <String[]>]

[-TableLevelSharingPropertyMaterializedViewsToExclude <String[]>]

[-TableLevelSharingPropertyMaterializedViewsToInclude <String[]>]

[-TableLevelSharingPropertyTablesToExclude <String[]>] [-TableLevelSharingPropertyTablesToInclude <String[]>]

[-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]

[-WhatIf] [-Confirm] [<CommonParameters>]

Invoke-AzKustoInviteDatabaseFollower -ClusterName <String> -DatabaseName <String> -ResourceGroupName <String> [-SubscriptionId <String>] -Parameter

<IDatabaseInviteFollowerRequest> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>]

[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Invoke-AzKustoInviteDatabaseFollower -InputObject <IKustoIdentity> -InviteeEmail <String> [-TableLevelSharingPropertyExternalTablesToExclude <String[]>]

[-TableLevelSharingPropertyExternalTablesToInclude <String[]>] [-TableLevelSharingPropertyFunctionsToExclude <String[]>] [-TableLevelSharingPropertyFunctionsToInclude

<String[]>] [-TableLevelSharingPropertyMaterializedViewsToExclude <String[]>]

[-TableLevelSharingPropertyMaterializedViewsToInclude <String[]>]

[-TableLevelSharingPropertyTablesToExclude <String[]>] [-TableLevelSharingPropertyTablesToInclude <String[]>] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]

[-WhatIf] [-Confirm] [<CommonParameters>]

Invoke-AzKustoInviteDatabaseFollower -InputObject <IKustoIdentity> -Parameter <IDatabaseInviteFollowerRequest> [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials]

[-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Generates an invitation token that allows attaching a follower database to this database.

PARAMETERS

-ClusterName <String>

The name of the Kusto cluster.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-DatabaseName <String>

The name of the database in the Kusto cluster.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IKustoIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Parameter <IDatabaseInviteFollowerRequest>

The request to invite a follower to a database.

To construct, see NOTES section for PARAMETER properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-InviteeEmail <String>

The email of the invited user for which the follower invitation is generated.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TableLevelSharingPropertyExternalTablesToExclude <String[]>

List of external tables to exclude from the follower database

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-TableLevelSharingPropertyExternalTablesToInclude <String[]>

List of external tables to include in the follower database

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-TableLevelSharingPropertyFunctionsToExclude <String[]>

List of functions to exclude from the follower database

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-TableLevelSharingPropertyFunctionsToInclude <String[]>

List of functions to include in the follower database

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-TableLevelSharingPropertyMaterializedViewsToExclude <String[]>

List of materialized views to exclude from the follower database

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TableLevelSharingPropertyMaterializedViewsToInclude <String[]>

List of materialized views to include in the follower database

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TableLevelSharingPropertyTablesToExclude <String[]>

List of tables to exclude from the follower database

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TableLevelSharingPropertyTablesToInclude <String[]>

List of tables to include in the follower database

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.Api20230815.IDatabaseInviteFollowerRequest

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.IKustoIdentity

OUTPUTS

System.String

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IKustoIdentity>: Identity Parameter

[AttachedDatabaseConfigurationName <String>]: The name of the attached database configuration.

[ClusterName <String>]: The name of the Kusto cluster.

[DataConnectionName <String>]: The name of the data connection.

[DatabaseName <String>]: The name of the database in the Kusto cluster.

[Id <String>]: Resource identity path

[Location <String>]: The name of Azure region.

[ManagedPrivateEndpointName <String>]: The name of the managed private endpoint.

[OperationId <String>]: The ID of an ongoing async operation.

[PrincipalAssignmentName <String>]: The name of the Kusto principalAssignment.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection.

[PrivateLinkResourceName <String>]: The name of the private link resource.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SandboxCustomImageName <String>]: The name of the sandbox custom image.

[ScriptName <String>]: The name of the Kusto database script.

[SubscriptionId <String>]: The ID of the target subscription.

PARAMETER <IDatabaseInviteFollowerRequest>: The request to invite a follower to a database.

InviteeEmail <String>: The email of the invited user for which the follower invitation is generated.

[TableLevelSharingPropertyExternalTablesToExclude <String[]>]: List of external tables to exclude from the follower database

[TableLevelSharingPropertyExternalTablesToInclude <String[]>]: List of external tables to include in the follower database

[TableLevelSharingPropertyFunctionsToExclude <String[]>]: List of functions to exclude from the follower database

[TableLevelSharingPropertyFunctionsToInclude <String[]>]: List of functions to include in the follower database

[TableLevelSharingPropertyMaterializedViewsToExclude <String[]>]: List of materialized views to exclude from the follower database

[TableLevelSharingPropertyMaterializedViewsToInclude <String[]>]: List of materialized views to include in the follower database

[TableLevelSharingPropertyTablesToExclude <String[]>]: List of tables to exclude from the follower database

[TableLevelSharingPropertyTablesToInclude <String[]>]: List of tables to include in the follower database

----- EXAMPLE 1 -----

```
PS C:\>Invoke-AzKustoInviteDatabaseFollower -ClusterName "myCluster" -DatabaseName "myDatabase"
-ResourceGroupName "myResourceGroup" -InviteeEmail "user@contoso.com"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.kusto/invoke-azkustoinvitedatabasefollower>