



Windows PowerShell Get-Help on Cmdlet 'Invoke-AzStackHciExtendClusterSoftwareAssuranceBenefit'

PS:\>Get-HELP Invoke-AzStackHciExtendClusterSoftwareAssuranceBenefit -Full

NAME

Invoke-AzStackHciExtendClusterSoftwareAssuranceBenefit

SYNOPSIS

Extends Software Assurance Benefit to a cluster

SYNTAX

```
Invoke-AzStackHciExtendClusterSoftwareAssuranceBenefit -ClusterName <String> -ResourceGroupName <String>
[-SubscriptionId <String>] [-SoftwareAssuranceIntent
    <SoftwareAssuranceIntent>] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]
    [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

```
Invoke-AzStackHciExtendClusterSoftwareAssuranceBenefit -ClusterName <String> -ResourceGroupName <String>
[-SubscriptionId <String>] -SoftwareAssuranceChangeRequest
    <SoftwareAssuranceChangeRequest> [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>]
    [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
```

[<CommonParameters>]

Invoke-AzStackHciExtendClusterSoftwareAssuranceBenefit -InputObject <IStackHciIdentity> [-SoftwareAssuranceIntent
<SoftwareAssuranceIntent>] [-DefaultProfile
<PObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>]
[-NoWait] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Invoke-AzStackHciExtendClusterSoftwareAssuranceBenefit -InputObject <IStackHciIdentity>
-SoftwareAssuranceChangeRequest <ISoftwareAssuranceChangeRequest>
[-DefaultProfile <PObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Extends Software Assurance Benefit to a cluster

PARAMETERS

-ClusterName <String>

The name of the cluster.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IStackHcIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-SoftwareAssuranceChangeRequest <ISoftwareAssuranceChangeRequest>

.

To construct, see NOTES section for SOFTWAREASSURANCECHANGEREQUEST properties and create a hash table.

Required? true
Position? named
Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-SoftwareAssuranceIntent <SoftwareAssuranceIntent>

Customer Intent for Software Assurance Benefit.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.StackHCI.Models.Api20230301.ISoftwareAssuranceChangeRequest

Microsoft.Azure.PowerShell.Cmdlets.StackHCI.Models.IStackHciIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.StackHCI.Models.Api20230301.ICluster

NOTES

COMPLEX PARAMETER PROPERTIES

information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IStackHciIdentity>: Identity Parameter

[ArcSettingName <String>]: The name of the proxy resource holding details of HCI ArcSetting information.

[ClusterName <String>]: The name of the cluster.

[ExtensionName <String>]: The name of the machine extension.

[Id <String>]: Resource identity path

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

SOFTWAREASSURANCECHANGEREQUEST <ISoftwareAssuranceChangeRequest>: .

[SoftwareAssuranceIntent <SoftwareAssuranceIntent?>]: Customer Intent for Software Assurance Benefit.

----- EXAMPLE 1 -----

```
PS C:\>Invoke-AzStackHciExtendClusterSoftwareAssuranceBenefit -ClusterName "test-clus" -ResourceGroupName "test-rg"
```

----- EXAMPLE 2 -----

```
PS C:\>Invoke-AzStackHciExtendClusterSoftwareAssuranceBenefit -ClusterName "test-clus" -ResourceGroupName "test-rg" -SoftwareAssuranceIntent "Disable"
```


RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.stackhci/invoke-azstackhciextendclustersoftwareassurancebenefit>