



Windows PowerShell Get-Help on Cmdlet 'Join-AzDataLakeStoreItem'

PS:\>Get-HELP Join-AzDataLakeStoreItem -Full

NAME

Join-AzDataLakeStoreItem

SYNOPSIS

Joins one or more files to create one file in Data Lake Store.

SYNTAX

```

Join-AzDataLakeStoreItem [-Account] <System.String> [-Paths]
<Microsoft.Azure.Commands.DataLakeStore.Models.DataLakeStorePathInstance[]> [-Destination]
<Microsoft.Azure.Commands.DataLakeStore.Models.DataLakeStorePathInstance> [[-Force]] [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Confirm] [-WhatIf]
[<CommonParameters>]

```

DESCRIPTION

The Join-AzDataLakeStoreItem cmdlet joins one or more files to create one file in Data Lake Store.

-Account <System.String>

Specifies the name of the Data Lake Store account.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Destination <Microsoft.Azure.Commands.DataLakeStore.Models.DataLakeStorePathInstance>

Specifies the Data Lake Store path for the joined item, starting with the root directory (/).

Required? true

Position? 2

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Force <System.Management.Automation.SwitchParameter>

Indicates that this operation can overwrite the destination file if it already exists.

Required? false

Position? 3

Default value False

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Paths <Microsoft.Azure.Commands.DataLakeStore.Models.DataLakeStorePathInstance[]>

Specifies an array of Data Lake Store paths of the files to combine, starting with the root directory (/).

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

Microsoft.Azure.Commands.DataLakeStore.Models.DataLakeStorePathInstance[]

Microsoft.Azure.Commands.DataLakeStore.Models.DataLakeStorePathInstance

System.Management.Automation.SwitchParameter

OUTPUTS

System.String

NOTES

----- Example 1: Join two items -----

Join-AzDataLakeStoreItem -AccountName "ContosoADL" -Paths "/MyFiles/File01.txt","/MyFiles/File02.txt" -Destination
"/MyFiles/CombinedFile.txt"

This command joins File01.txt and File02.txt to create the file CombinedFile.txt.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.datalakestore/join-azdatalakestoreitem>

[Get-AzDataLakeStoreItem](#)

[Export-AzDataLakeStoreItem](#)

[Import-AzDataLakeStoreItem](#)

[New-AzDataLakeStoreItem](#)

[Remove-AzDataLakeStoreItem](#)

[Test-AzDataLakeStoreItem](#)