



Windows PowerShell Get-Help on Cmdlet 'New-AzApiManagementOpenIdConnectProvider'

PS:\>Get-HELP New-AzApiManagementOpenIdConnectProvider -Full

NAME

New-AzApiManagementOpenIdConnectProvider

SYNOPSIS

Creates an OpenID Connect provider.

SYNTAX

```
New-AzApiManagementOpenIdConnectProvider -ClientId <System.String> [-ClientSecret <System.String>] -Context  
<Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext> [-DefaultProfile  
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Description  
<System.String>] -MetadataEndpointUri <System.String> -Name  
    <System.String> [-OpenIdConnectProviderId <System.String>] [<CommonParameters>]
```

DESCRIPTION

The `New-AzApiManagementOpenIdConnectProvider` cmdlet creates an OpenID Connect provider in Azure API Management.

PARAMETERS

-ClientId <System.String>

Specifies the client ID of the developer console.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ClientSecret <System.String>

Specifies the client secret of the developer console.

Required? false

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Context <Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext>

Specifies a PsApiManagementContext object.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName, ByValue)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None
Accept pipeline input? False
Accept wildcard characters? false

-Description <System.String>

Specifies a description.

Required? false
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-MetadataEndpointUri <System.String>

Specifies a metadata endpoint URI of the provider.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Name <System.String>

Specifies a friendly name for the provider.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-OpenIdConnectProviderId <System.String>

Specifies an ID for the provider. If you do not specify an ID, this cmdlet generates one.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementContext

System.String

OUTPUTS

Microsoft.Azure.Commands.ApiManagement.ServiceManagement.Models.PsApiManagementOpenIdConnectProvider

NOTES

----- Example 1: Create a provider -----

