



Windows PowerShell Get-Help on Cmdlet 'New-AzAppConfigurationStore'

PS:\>Get-HELP New-AzAppConfigurationStore -Full

NAME

New-AzAppConfigurationStore

SYNOPSIS

Creates a configuration store with the specified parameters.

SYNTAX

```
New-AzAppConfigurationStore -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] -Location
<String> -Sku <String> [-CreateMode <CreateMode>]
[-DisableLocalAuth] [-EnablePurgeProtection] [-EncryptionKeyIdentifier <String>] [-IdentityType <IdentityType>]
[-KeyVaultIdentityClientId <String>]
[-PublicNetworkAccess <PublicNetworkAccess>] [-SoftDeleteRetentionInDay <Int32>] [-Tag <Hashtable>]
[-UserAssignedIdentity <String[]>] [-DefaultProfile <PSObject>]
[-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]
[-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

Creates a configuration store with the specified parameters.

PARAMETERS

-Name <String>

The name of the configuration store.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group to which the container registry belongs.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The Microsoft Azure subscription ID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Location <String>

The geo-location where the resource lives

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Sku <String>

The SKU name of the configuration store.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-CreateMode <CreateMode>

Indicates whether the configuration store need to be recovered.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-DisableLocalAuth [<SwitchParameter>]

Disables all authentication methods other than AAD authentication.

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-EnablePurgeProtection [<SwitchParameter>]

Property specifying whether protection against purge is enabled for this configuration store.

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-EncryptionKeyIdentifier <String>

The URI of the key vault key used to encrypt data.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IdentityType <IdentityType>

The type of managed identity used.

The type 'SystemAssigned, UserAssigned' includes both an implicitly created identity and a set of user-assigned identities.

The type 'None' will remove any identities.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-KeyVaultIdentityClientId <String>

The client id of the identity which will be used to access key vault.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-PublicNetworkAccess <PublicNetworkAccess>

Control permission for data plane traffic coming from public networks while private endpoint is enabled.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SoftDeleteRetentionInDay <Int32>

The amount of time in days that the configuration store will be retained when it is soft deleted.

Required? false
Position? named
Default value 0
Accept pipeline input? false
Accept wildcard characters? false

-Tag <Hashtable>

Resource tags.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-UserAssignedIdentity <String[]>

The list of user-assigned identities associated with the resource.

The user-assigned identity dictionary keys will be ARM resource ids in the form:

'/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/providers/Microsoft.ManagedIdentity/userAssignedIdentities/{identityName}'.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.AppConfiguration.Models.Api20220501.IConfigurationStore

----- EXAMPLE 1 -----

PS C:\>New-AzAppConfigurationStore -Name azptest-appstore -ResourceGroupName azptest_gp -Location eastus -Sku Standard

----- EXAMPLE 2 -----

```
PS C:\>$storeName = "azptest-appstore-recover"
```

```
$resourceGroupName = "azptest_gp"
```

```
$location = "eastus"
```

```
New-AzAppConfigurationStore -Name $storeName -ResourceGroupName $resourceGroupName -Location $location  
-Sku Standard
```

```
Remove-AzAppConfigurationStore -Name $storeName -ResourceGroupName $resourceGroupName
```

```
Get-AzAppConfigurationDeletedStore -Location $location -Name $storeName
```

```
New-AzAppConfigurationStore -Name $storeName -ResourceGroupName $resourceGroupName -Location $location  
-Sku Standard -CreateMode 'Recover'
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.appconfiguration/new-azappconfigurationstore>