



Windows PowerShell Get-Help on Cmdlet 'New-AzApplicationGatewayClientAuthConfiguration'

PS:\>Get-HELP New-AzApplicationGatewayClientAuthConfiguration -Full

WARNING: The names of some imported commands from the module 'Microsoft.Azure.PowerShell.Cmdlets.Network' include unapproved verbs that might make them less discoverable.

To find the commands with unapproved verbs, run the Import-Module command again with the Verbose parameter. For a list of approved verbs, type Get-Verb.

NAME

New-AzApplicationGatewayClientAuthConfiguration

SYNOPSIS

Creates a new client authentication configuration for SSL profile.

SYNTAX

New-AzApplicationGatewayClientAuthConfiguration [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]

[-VerifyClientCertIssuerDN] [-VerifyClientRevocation {None | OCSP}] [<CommonParameters>]

DESCRIPTION

The New-AzApplicationGatewayClientAuthConfiguration cmdlet creates a new client authentication configuration for SSL profile.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-VerifyClientCertIssuerDN <System.Management.Automation.SwitchParameter>

Verify client certificate issuer name.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-VerifyClientRevocation <System.String>

Verify client certificate revocation status.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

None

OUTPUTS

Microsoft.Azure.Commands.Network.Models.PSApplicationGatewayClientAuthConfiguration

NOTES

----- Example 1 -----

```
$clientAuthConfig = New-AzApplicationGatewayClientAuthConfiguration -VerifyClientCertIssuerDN  
-VerifyClientRevocation OCSP
```

The command create a new client auth configuration and stores it in \$clientAuthConfig variable to be used in a SSL profile.

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.network/new-azapplicationgatewayclientauthconfiguration>

Get-AzApplicationGatewayClientAuthConfiguration

Remove-AzApplicationGatewayClientAuthConfiguration

