



## ***Windows PowerShell Get-Help on Cmdlet 'New-AzApplicationInsightsContinuousExport'***

***PS:\>Get-HELP New-AzApplicationInsightsContinuousExport -Full***

### NAME

New-AzApplicationInsightsContinuousExport

### SYNOPSIS

Create a Continuous Export configuration of an Application Insights component.

### SYNTAX

```
New-AzApplicationInsightsContinuousExport -ResourceGroupName <String> -Name <String> [-SubscriptionId <String>]
[-DestinationType <String>] [-NotificationQueueEnabled
<String>] [-NotificationQueueUri <String>] [-DocumentType <String[]>] [-StorageAccountId <String>] [-StorageLocation
<String>] [-StorageSASUri <String>]
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

### DESCRIPTION

Create a Continuous Export configuration of an Application Insights component.

## PARAMETERS

### -ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

### -Name <String>

The name of the Application Insights component resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

### -SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

### -DestinationType <String>

The Continuous Export destination type.

This has to be 'Blob'.

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-NotificationQueueEnabled <String>

Deprecated

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-NotificationQueueUri <String>

Deprecated

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-DocumentType <String[]>

The document types to be exported, as comma separated values.

Allowed values include 'Requests', 'Custom Event', 'Exception', 'Metric', 'Page View', 'Page Load', 'Dependency', 'Performance Counter', 'Availability', 'Trace'.

Required? false  
Position? named  
Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -StorageAccountId <String>

The name of destination storage account.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -StorageLocation <String>

The location ID of the destination storage container.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -StorageSASUri <String>

The SAS URL for the destination storage container.

It must grant write permission.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

#### -Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false  
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.ApplicationInsights.Models.Api20150501.IApplicationInsightsComponentExportConfiguration

----- EXAMPLE 1 -----

```
PS C:\>$sastoken = New-AzStorageContainerSASToken -Name testcontainer -Context $context -ExpiryTime  
(Get-Date).AddYears(50) -Permission w
```

```
$sasuri = "https://teststorageaccount.blob.core.windows.net/testcontainer" + $sastoken  
New-AzApplicationInsightsContinuousExport -ResourceGroupName "testgroup" -Name "test" `  
-DocumentType "Request","Trace", "Custom Event" -StorageAccountId
```

"/subscriptions/50359d91-7b9d-4823-85af-eb298a61ba96/resourceGroups/testgroup/providers/Microsoft.Storage/storageAccounts/teststorageaccount" -StorageLocation  
sourcecentralus `  
-StorageSASUri \$sasuri -DestinationType Blob

#### RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.applicationinsights/new-azapplicationinsightscontinuousexport>