



Windows PowerShell Get-Help on Cmdlet 'New-AzCdnUrlRedirectActionObject'

PS:\>Get-HELP New-AzCdnUrlRedirectActionObject -Full

NAME

New-AzCdnUrlRedirectActionObject

SYNOPSIS

Create an in-memory object for UrlRedirectAction.

SYNTAX

```
New-AzCdnUrlRedirectActionObject -ParameterRedirectType <RedirectType> -Name <DeliveryRuleAction>
[-ParameterCustomFragment <String>] [-ParameterCustomHostname
<String>] [-ParameterCustomPath <String>] [-ParameterCustomQueryString <String>] [-ParameterDestinationProtocol
<DestinationProtocol>] [<CommonParameters>]
```

DESCRIPTION

Create an in-memory object for UrlRedirectAction.

PARAMETERS

-ParameterRedirectType <RedirectType>

The redirect type the rule will use when redirecting traffic.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <DeliveryRuleAction>

The name of the action for the delivery rule.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ParameterCustomFragment <String>

Fragment to add to the redirect URL.

Fragment is the part of the URL that comes after #.

Do not include the #.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ParameterCustomHostname <String>

Host to redirect.

Leave empty to use the incoming host as the destination host.

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ParameterCustomPath <String>

The full path to redirect.
Path cannot be empty and must start with /.
Leave empty to use the incoming path as destination path.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ParameterCustomQueryString <String>

The set of query strings to be placed in the redirect URL.
Setting this value would replace any existing query string; leave empty to preserve the incoming query string.
Query string must be in <key>=<value> format.
? and & will be added automatically so do not include them.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ParameterDestinationProtocol <DestinationProtocol>

Protocol to use for the redirect.
The default value is MatchRequest.

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Cdn.Models.Api20240201.UrlRedirectAction

----- EXAMPLE 1 -----

```
PS C:\>New-AzCdnUrlRedirectActionObject -Name rule01 -ParameterRedirectType redirect
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/Az.Cdn/new-AzCdnUrlRedirectActionObject>