



Windows PowerShell Get-Help on Cmdlet 'New-AzContainerRegistryExportPipeline'

PS:\>Get-HELP New-AzContainerRegistryExportPipeline -Full

NAME

New-AzContainerRegistryExportPipeline

SYNOPSIS

Creates an export pipeline for a container registry with the specified parameters.

SYNTAX

```
New-AzContainerRegistryExportPipeline -Name <String> -RegistryName <String> -ResourceGroupName <String>
[-SubscriptionId <String>] [-IdentityPrincipalId <String>]
[-IdentityTenantId <String>] [-IdentityType <ResourceIdentityType>] [-IdentityUserAssignedIdentity <Hashtable>]
[-Location <String>] [-Option <PipelineOptions[]>]
[-TargetKeyVaultUri <String>] [-TargetType <String>] [-TargetUri <String>] [-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

Creates an export pipeline for a container registry with the specified parameters.

PARAMETERS

-Name <String>

The name of the export pipeline.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-RegistryName <String>

The name of the container registry.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

The value must be an UUID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IdentityPrincipalId <String>

The principal ID of resource identity.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IdentityTenantId <String>

The tenant ID of resource.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IdentityType <ResourceIdentityType>

The identity type.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IdentityUserAssignedIdentity <Hashtable>

The list of user identities associated with the resource.

The user identity dictionary key references will be ARM resource ids in the form:

'/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/

providers/Microsoft.ManagedIdentity/userAssignedIdentities/{identityName}'.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Location <String>

The location of the export pipeline.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Option <PipelineOptions[]>

The list of all options configured for the pipeline.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TargetKeyVaultUri <String>

They key vault secret uri to obtain the target storage SAS token.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TargetType <String>

The type of target for the export pipeline.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TargetUri <String>

The target uri of the export pipeline. When 'AzureStorageBlob':

"https://accountName.blob.core.windows.net/containerName/blobName" When 'AzureStorageBlobContainer':

"https://accountName.blob.core.windows.net/containerName"

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see

about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.ContainerRegistry.Models.Api202301Preview.IExportPipeline

----- EXAMPLE 1 -----

```
PS C:\>New-AzContainerRegistryExportPipeline -name Exam -RegistryName RegistryExample -ResourceGroupName  
MyResourceGroup -IdentityType 'SystemAssigned' -TargetType
```

```
AzureStorageBlobContainer -TargetUri https://sa.blob.core.windows.net/public/ -TargetKeyVaultUri
```

```
https://examplekeyvault.vault.azure.net/secrets/test/18d55a35beba4b20bdd044a2a9d14c30
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.containerregistry/new-azcontainerregistryexportpipeline>