



Windows PowerShell Get-Help on Cmdlet 'New-AzDnsDnssecConfig'

PS:\>Get-HELP New-AzDnsDnssecConfig -Full

NAME

New-AzDnsDnssecConfig

SYNOPSIS

Creates or updates the DNSSEC configuration on a DNS zone.

SYNTAX

New-AzDnsDnssecConfig -ResourceGroupName <String> [-SubscriptionId <String>] -ZoneName <String> [-IfMatch <String>] [-IfNoneMatch <String>] [-DefaultProfile

<PSCredential>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

New-AzDnsDnssecConfig -InputObject <IDnsIdentity> [-IfMatch <String>] [-IfNoneMatch <String>] [-DefaultProfile <PSCredential>] [-AsJob] [-Break] [-HttpPipelineAppend

<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Creates or updates the DNSSEC configuration on a DNS zone.

PARAMETERS

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ZoneName <String>

The name of the DNS zone (without a terminating dot).

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IDnsIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-IfMatch <String>

The etag of the DNSSEC configuration.

Omit this value to always overwrite the DNSSEC configuration.

Specify the last-seen etag value to prevent accidentally overwriting any concurrent changes.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IfNoneMatch <String>

Set to '*' to allow this DNSSEC configuration to be created, but to prevent updating existing DNSSEC configuration.

Other values will be ignored.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Dns.Models.IDnsIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Dns.Models.Api20230701Preview.IDnssecConfig

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IDnsIdentity>: Identity Parameter

[Id <String>]: Resource identity path

[RecordType <RecordType?>]: The type of DNS record in this record set.

[RelativeRecordSetName <String>]: The name of the record set, relative to the name of the zone.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

[ZoneName <String>]: The name of the DNS zone (without a terminating dot).

----- EXAMPLE 1 -----

PS C:\>New-AzDnsDnssecConfig -ResourceGroupName dnssecrg -ZoneName contoso.com

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.dns/new-azdnssdssecconfig>