



Windows PowerShell Get-Help on Cmdlet 'New-AzEventGridWebHookEventSubscriptionDestinationObject'

PS:\>Get-HELP New-AzEventGridWebHookEventSubscriptionDestinationObject -Full

NAME

New-AzEventGridWebHookEventSubscriptionDestinationObject

SYNOPSIS

Create an in-memory object for WebHookEventSubscriptionDestination.

SYNTAX

```
New-AzEventGridWebHookEventSubscriptionDestinationObject [-AzureActiveDirectoryApplicationIdOrUri <String>]
[-AzureActiveDirectoryTenantId <String>]
[-DeliveryAttributeMapping <IDeliveryAttributeMapping[]>] [-EndpointUrl <String>] [-MaxEventsPerBatch <Int32>]
[-MinimumTlsVersionAllowed <String>]
[-PreferredBatchSizeInKilobyte <Int32>] [<CommonParameters>]
```

DESCRIPTION

Create an in-memory object for WebHookEventSubscriptionDestination.

-AzureActiveDirectoryApplicationIdOrUri <String>

The Azure Active Directory Application ID or URI to get the access token that will be included as the bearer token in delivery requests.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AzureActiveDirectoryTenantId <String>

The Azure Active Directory Tenant ID to get the access token that will be included as the bearer token in delivery requests.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DeliveryAttributeMapping <IDeliveryAttributeMapping[]>

Delivery attribute details.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-EndpointUrl <String>

The URL that represents the endpoint of the destination of an event subscription.

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-MaxEventsPerBatch <Int32>

Maximum number of events per batch.

Required? false
Position? named
Default value 0
Accept pipeline input? false
Accept wildcard characters? false

-MinimumTlsVersionAllowed <String>

Minimum TLS version that should be supported by webhook endpoint.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-PreferredBatchSizeInKilobyte <Int32>

Preferred batch size in Kilobytes.

Required? false
Position? named
Default value 0
Accept pipeline input? false
Accept wildcard characters? false

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.EventGrid.Models.WebHookEventSubscriptionDestination

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

DELIVERYATTRIBUTEMAPPING <IDeliveryAttributeMapping[]>: Delivery attribute details.

Type <String>: Type of the delivery attribute or header name.

[Name <String>]: Name of the delivery attribute or header.

----- EXAMPLE 1 -----

```
PS      C:\>New-AzEventGridWebHookEventSubscriptionDestinationObject -EndpointUrl
"https://azpsweb.azurewebsites.net/api/updates"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/Az.EventGrid/new-azeventgridwebhookeventssubscriptiondestinationobject>