



Windows PowerShell Get-Help on Cmdlet 'New-AzEventHubKey'

PS:\>Get-HELP New-AzEventHubKey -Full

NAME

New-AzEventHubKey

SYNOPSIS

Regenerates an EventHub SAS key

SYNTAX

New-AzEventHubKey -Name <String> -NamespaceName <String> -ResourceGroupName <String> [-SubscriptionId <String>] [-KeyType <String>] [-KeyValue <String>]

[-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]

[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

New-AzEventHubKey -Name <String> -NamespaceName <String> -ResourceGroupName <String> [-SubscriptionId <String>] -EventHubName <String> [-KeyType <String>] [-KeyValue

<String>] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]

[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Regenerates an EventHub SAS key

PARAMETERS

-Name <String>

The name of the Authorization Rule

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NamespaceName <String>

The name of EventHub namespace

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-EventHubName <String>

The name of the EventHub entity.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-KeyType <String>

The access key to regenerate.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-KeyValue <String>

Optional, if the key value provided, is set for KeyType or autogenerated Key value set for keyType

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.EventHub.Models.IAccessKeys

----- EXAMPLE 1 -----

```
PS C:\>New-AzEventHubKey -ResourceGroupName myResourceGroup -NamespaceName myNamespace -Name
rootmanagesharedaccesskey -KeyType PrimaryKey
```

----- EXAMPLE 2 -----

```
PS C:\>New-AzEventHubKey -ResourceGroupName myResourceGroup -NamespaceName myNamespace
-EventHubName myEventHub -Name rootmanagesharedaccesskey -KeyType SecondaryKey
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.eventhub/new-azeventhubkey>