



Windows PowerShell Get-Help on Cmdlet 'New-AzHealthcarelotConnector'

PS: \>Get-HELP New-AzHealthcarelotConnector -Full

NAME

New-AzHealthcarelotConnector

SYNOPSIS

Creates or updates an IoT Connector resource with the specified parameters.

SYNTAX

```
New-AzHealthcarelotConnector -Name <String> -ResourceGroupName <String> -WorkspaceName <String>
[-SubscriptionId <String>] -DeviceMappingContent <Hashtable>
-IngestionEndpointConfigurationConsumerGroup <String> -IngestionEndpointConfigurationEventHubName <String>
-IngestionEndpointConfigurationFullyQualifiedEventHubNamespace <String> -Location <String> [-Etag <String>]
[-IdentityType <ServiceManagedIdentityType>]
[-IdentityUserAssignedIdentity <Hashtable>] [-Tag <Hashtable>] [-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

DESCRIPTION

Creates or updates an IoT Connector resource with the specified parameters.

PARAMETERS

-Name <String>

The name of IoT Connector resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group that contains the service instance.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-WorkspaceName <String>

The name of workspace resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The subscription identifier.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DeviceMappingContent <Hashtable>

The mapping.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IngestionEndpointConfigurationConsumerGroup <String>

Consumer group of the event hub to connected to.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IngestionEndpointConfigurationEventHubName <String>

Event Hub name to connect to.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IngestionEndpointConfigurationFullyQualifiedEventHubNamespace <String>

Fully qualified namespace of the Event Hub to connect to.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Location <String>

The resource location.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Etag <String>

An etag associated with the resource, used for optimistic concurrency when editing it.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IdentityType <ServiceManagedIdentityType>

Type of identity being specified, currently SystemAssigned and None are allowed.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IdentityUserAssignedIdentity <Hashtable>

The set of user assigned identities associated with the resource.

The userAssignedIdentities dictionary keys will be ARM resource ids in the form:

'/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/providers/Microsoft.ManagedIdentity/userAssignedIdentities/{identityName}.

The dictionary values can be empty objects ({} in requests.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

Resource tags.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.HealthcareApis.Models.Api20211101.IlotConnector

----- EXAMPLE 1 -----

```
PS C:\>$arr = @()
```

```
New-AzHealthcareIotConnector -Name azpsiotconnector -ResourceGroupName azps_test_group -WorkspaceName  
azpshcws -Location eastus2  
-IngestionEndpointConfigurationConsumerGroup "sajob-01-portal_input-01_consumer_group"  
-IngestionEndpointConfigurationEventHubName "sajob01portaleventhub"  
-IngestionEndpointConfigurationFullyQualifiedEventHubNamespace "sdk-Namespace-4761.servicebus.windows.net"  
-DeviceMappingContent  
@{"templateType"="CollectionContent";"template"=$arr}
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.healthcareapis/new-azhealthcareiotconnector>