



Windows PowerShell Get-Help on Cmdlet 'New-AzKustoPrivateEndpointConnection'

PS:\>Get-HELP New-AzKustoPrivateEndpointConnection -Full

NAME

New-AzKustoPrivateEndpointConnection

SYNOPSIS

Approve or reject a private endpoint connection with a given name.

SYNTAX

```
New-AzKustoPrivateEndpointConnection -ClusterName <String> -Name <String> -ResourceGroupName <String>
[-SubscriptionId <String>]
[-PrivateLinkServiceConnectionStateDescription <String>] [-PrivateLinkServiceConnectionStateStatus <String>]
[-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
New-AzKustoPrivateEndpointConnection -ClusterName <String> -Name <String> -ResourceGroupName <String>
[-SubscriptionId <String>] -Parameter
<IPrivateEndpointConnection> [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]
```

[`-Proxy` `<Uri>`] [`-ProxyCredential` `<PSCredential>`] [`-ProxyUseDefaultCredentials`] [`-WhatIf`] [`-Confirm`]
[`<CommonParameters>`]

DESCRIPTION

Approve or reject a private endpoint connection with a given name.

PARAMETERS

`-ClusterName` `<String>`

The name of the Kusto cluster.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-Name` `<String>`

The name of the private endpoint connection.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-ResourceGroupName` `<String>`

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Parameter <IPrivateEndpointConnection>

A private endpoint connection

To construct, see NOTES section for PARAMETER properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-PrivateLinkServiceConnectionStateDescription <String>

The private link service connection description.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-PrivateLinkServiceConnectionStateStatus <String>

The private link service connection status.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.Api20230815.IPrivateEndpointConnection

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Kusto.Models.Api20230815.IPrivateEndpointConnection

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

PARAMETER <IPrivateEndpointConnection>: A private endpoint connection

[PrivateLinkServiceConnectionStateDescription <String>]: The private link service connection description.

[PrivateLinkServiceConnectionStateStatus <String>]: The private link service connection status.

[SystemDataCreatedAt <DateTime?>]: The timestamp of resource creation (UTC).

[SystemDataCreatedBy <String>]: The identity that created the resource.

[SystemDataCreatedByType <CreatedByType?>]: The type of identity that created the resource.

[SystemDataLastModifiedAt <DateTime?>]: The timestamp of resource last modification (UTC)

[SystemDataLastModifiedBy <String>]: The identity that last modified the resource.

[SystemDataLastModifiedByType <CreatedByType?>]: The type of identity that last modified the resource.

----- EXAMPLE 1 -----

```
PS C:\>New-AzKustoPrivateEndpointConnection -ClusterName "mycluster" -ResourceGroupName "testrg"
-SubscriptionId "12345678-1234-1234-1234-123456789098" -Parameter
$privateEndpointConnection -Name "testprivateconnection-12345678-1234-1234-1234-123456789098"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.kusto/new-azkustoprivateendpointconnection>