



Windows PowerShell Get-Help on Cmdlet 'New-AzMLWorkspaceCodeVersion'

PS:\>Get-HELP New-AzMLWorkspaceCodeVersion -Full

NAME

New-AzMLWorkspaceCodeVersion

SYNOPSIS

Create or update version.

SYNTAX

```
New-AzMLWorkspaceCodeVersion -Name <String> -ResourceGroupName <String> -Version <String> -WorkspaceName
<String> [-SubscriptionId <String>] [-CodeUri <String>]
[-Description <String>] [-IsAnonymou] [-IsArchived] [-ResourceBaseProperty <Hashtable>] [-Tag <Hashtable>]
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

DESCRIPTION

Create or update version.

PARAMETERS

-Name <String>

Container name.

This is case-sensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Version <String>

Version identifier.

This is case-sensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-WorkspaceName <String>

Name of Azure Machine Learning workspace.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-CodeUri <String>

Uri where code is located

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Description <String>

The asset description text.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IsAnonymou [<SwitchParameter>]

If the name version are system generated (anonymous registration).

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-IsArchived [<SwitchParameter>]

Is the asset archived

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-ResourceBaseProperty <Hashtable>

The asset property dictionary.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

Tag dictionary.

Tags can be added, removed, and updated.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.MachineLearningServices.Models.Api20220501.ICodeVersion

----- EXAMPLE 1 -----

```
PS C:\>New-AzMLWorkspaceCodeVersion -ResourceGroupName ml-rg-test -WorkspaceName mlworkspace-portal01  
-Name 'cli-hello-example' -Version 1 -CodeUri
```

```
"https://mlworkspacepor8056718628.blob.core.windows.net/azureml-blobstore-dc0f7f2b-686d-417b-a456-6c09def791f5/Loc  
alUpload/a8da6e3978c9f8b1cb03501595a9142f/src"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.machinelearningservices/new-azmlworkspacecodeversion>