



Windows PowerShell Get-Help on Cmdlet 'New-AzPrivateLinkServiceConnection'

PS:\>Get-HELP New-AzPrivateLinkServiceConnection -Full

WARNING: The names of some imported commands from the module 'Microsoft.Azure.PowerShell.Cmdlets.Network' include unapproved verbs that might make them less discoverable.

To find the commands with unapproved verbs, run the Import-Module command again with the Verbose parameter. For a list of approved verbs, type Get-Verb.

NAME

New-AzPrivateLinkServiceConnection

SYNOPSIS

Creates a private link service connection configuration.

SYNTAX

```

New-AzPrivateLinkServiceConnection [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-GroupId
<System.String[]>] -Name <System.String> -PrivateLinkService
<Microsoft.Azure.Commands.Network.Models.PSPriateLinkService> [-RequestMessage <System.String>]
[<CommonParameters>]
```

```

New-AzPrivateLinkServiceConnection [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-GroupId
```

<System.String[]> -Name <System.String> -PrivateLinkServiceId <System.String> [-RequestMessage <System.String>]
[<CommonParameters>]

DESCRIPTION

The New-AzPrivateLinkServiceConnection cmdlet creates a private link service connection configuration.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-GroupId <System.String[]>

The list of group id. You can use '(Get-AzPrivateLinkResource -PrivateLinkResourceId \${privateLinkResourceId}).GroupId' to get the supported group ids.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

The name of private link service.

Required? true

Position? named

Default value None
Accept pipeline input? False
Accept wildcard characters? false

-PrivateLinkService <Microsoft.Azure.Commands.Network.Models.PSPPrivateLinkService>

The private link service.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-PrivateLinkServiceId <System.String>

The id of private link service.

Required? true
Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-RequestMessage <System.String>

The request message.

Required? false
Position? named
Default value None
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

None

OUTPUTS

Microsoft.Azure.Commands.Network.Models.PSPrivateLinkServiceConnection

NOTES

----- Example 1 -----

```
New-AzPrivateLinkServiceConnection -Name MyPLSConnection -PrivateLinkServiceId
```

```
"/subscriptions/00000000-0000-0000-0000-000000000000/resourceGroups/TestResourceGroup/providers/Microsoft.Network/privateLinkServices/privateLinkService"
```

```
-RequestMessage "Please Approve my request"
```

This example create a private link service connection object in memory for using in creating private endpoint.

----- Example 2 -----

```
New-AzPrivateLinkServiceConnection -GroupId <String[]> -Name 'MyPLSConnections' -PrivateLinkServiceId
```

'/subscriptions/00000000-0000-0000-0000-00000000000000000000/resourceGroups/TestResourceGroup/providers/Microsoft.Network/privateLinkServices/privateLinkService'

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.network/new-azprivatelinkserviceconnection>

New-AzPrivateEndpoint