



Windows PowerShell Get-Help on Cmdlet 'New-AzRestorePointCollection'

PS:\>Get-HELP New-AzRestorePointCollection -Full

NAME

New-AzRestorePointCollection

SYNOPSIS

Creates a New Restore Point Collection

SYNTAX

```
New-AzRestorePointCollection [-ResourceGroupName] <System.String> [-Name] <System.String> [-VmId]
<System.String> [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Location
<System.String>] [-Confirm] [-WhatIf] [<CommonParameters>]
```

```
New-AzRestorePointCollection [-ResourceGroupName] <System.String> [-Name] <System.String> [[-VmId]
<System.String>] [-RestorePointCollectionId] <System.String>
[-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
-Location <System.String> [-Confirm] [-WhatIf]
[<CommonParameters>]
```

DESCRIPTION

Creates a New Restore Point Collection

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Location <System.String>

location of the source resource used to create this restore point collection.

Required? false

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-Name <System.String>

Resource Name

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ResourceGroupName <System.String>

Resource Group Name

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-RestorePointCollectionId <System.String>

ARM Id of Source RestorePoint Collection

Required? true
Position? 3
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-VmId <System.String>

resource Id of the source resource used to create this restore point Collection

Required? true
Position? 2
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

OUTPUTS

Microsoft.Azure.Commands.Compute.Automation.Models.PSRestorePointCollection

NOTES

New-AzRestorePointCollection -ResourceGroupName <String> -Name <String> -VmId <String>

Create a new Restore Point Collection using a VM Id.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.compute/new-azrestorepointcollection>