



Windows PowerShell Get-Help on Cmdlet 'New-AzSecurityConnectorDevOpsConfiguration'

PS:\>Get-HELP New-AzSecurityConnectorDevOpsConfiguration -Full

NAME

New-AzSecurityConnectorDevOpsConfiguration

SYNOPSIS

Create a DevOps Configuration.

SYNTAX

```
New-AzSecurityConnectorDevOpsConfiguration -ResourceGroupName <String> -SecurityConnectorName <String>
[-SubscriptionId <String>] [-AuthorizationCode <String>]
    [-AutoDiscovery <String>] [-TopLevelInventoryList <String[]>] [-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
    [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
    [<CommonParameters>]
```

DESCRIPTION

Create a DevOps Configuration.

PARAMETERS

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SecurityConnectorName <String>

The security connector name.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Azure subscription ID

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AuthorizationCode <String>

Gets or sets one-time OAuth code to exchange for refresh and access tokens.Only used during PUT/PATCH operations.

The secret is cleared during GET.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AutoDiscovery <String>

AutoDiscovery states.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-TopLevelInventoryList <String[]>

List of top-level inventory to select when AutoDiscovery is disabled. This field is ignored when AutoDiscovery is enabled.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Security.Models.IDevOpsConfiguration

----- EXAMPLE 1 -----

```
PS C:\>New-AzSecurityConnectorDevOpsConfiguration -ResourceGroupName "securityconnectors-pwsh-tmp"
-SecurityConnectorName "ado-sdk-pwsh-test03" -AutoDiscovery
Disabled -TopLevelInventoryList @("org1", "org2") -AuthorizationCode "myAuthorizationCode"
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.security/new-azsecurityconnectordevopsconfiguration>