



Windows PowerShell Get-Help on Cmdlet 'New-AzSentinelBookmarkRelation'

PS:\>Get-HELP New-AzSentinelBookmarkRelation -Full

NAME

New-AzSentinelBookmarkRelation

SYNOPSIS

Creates the bookmark relation.

SYNTAX

```
New-AzSentinelBookmarkRelation -BookmarkId <String> -ResourceGroupName <String> -WorkspaceName <String>
[-RelationName <String>] [-SubscriptionId <String>]
[-RelatedResourceId <String>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>]
[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

New-AzSentinelBookmarkRelation -BookmarkId <String> -ResourceGroupName <String> -WorkspaceName <String>
[-RelationName <String>] [-SubscriptionId <String>] -Relation
<IRelation> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

DESCRIPTION

Creates the bookmark relation.

PARAMETERS

-BookmarkId <String>

Bookmark ID

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-WorkspaceName <String>

The name of the workspace.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-RelationName <String>

Relation Name

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Relation <IRelation>

Represents a relation between two resources

To construct, see NOTES section for RELATION properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-RelatedResourceId <String>

The resource ID of the related resource

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.
Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.SecurityInsights.Models.Api20210901Preview.IRelation

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.SecurityInsights.Models.Api20210901Preview.IRelation

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

RELATION <IRelation>: Represents a relation between two resources

[Etag <String>]: Etag of the azure resource

[SystemDataCreatedAt <DateTime?>]: The timestamp of resource creation (UTC).

[SystemDataCreatedBy <String>]: The identity that created the resource.

[SystemDataCreatedByType <CreatedByType?>]: The type of identity that created the resource.

[SystemDataLastModifiedAt <DateTime?>]: The timestamp of resource last modification (UTC)

[SystemDataLastModifiedBy <String>]: The identity that last modified the resource.

[SystemDataLastModifiedByType <CreatedByType?>]: The type of identity that last modified the resource.

[RelatedResourceId <String>]: The resource ID of the related resource

----- EXAMPLE 1 -----

```
PS C:\>$incident = Get-AzSentinelIncident -ResourceGroupName "myResourceGroup" -WorkspaceName
"myWorkspaceName" -Id "myIncidentId"
```

```
$bookmarkRelation = New-AzSentinelBookmarkRelation -ResourceGroupName "myResourceGroup" -WorkspaceName
"myWorkspaceName" -BookmarkId "myBookmarkId" -RelationName
((New-Guid).Guid) -RelatedResourceId ($incident.Id)
```

