



Windows PowerShell Get-Help on Cmdlet 'New-AzSqlDatabaseRestorePoint'

PS:\>Get-HELP New-AzSqlDatabaseRestorePoint -Full

NAME

New-AzSqlDatabaseRestorePoint

SYNOPSIS

Creates a new restore point from which a SQL Database can be restored.

SYNTAX

```
New-AzSqlDatabaseRestorePoint [-ResourceGroupName] <System.String> [-ServerName] <System.String>
[-DatabaseName] <System.String> [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -RestorePointLabel
<System.String> [-Confirm] [-WhatIf] [<CommonParameters>]
```

DESCRIPTION

The New-AzSqlDatabaseRestorePoint cmdlet creates a new restore point that an Azure SQL Data Warehouse can be restored from. This cmdlet is currently supported for Azure SQL Data Warehouse.

PARAMETERS

-DatabaseName <System.String>

Specifies the name of the SQL Database.

Required? true

Position? 2

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceGroupName <System.String>

Specifies the name of the resource group to which the SQL Database is assigned.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-RestorePointLabel <System.String>

Specifies the label of the restore point for easy identification.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ServerName <System.String>

Specifies the name of the AzureSQL Server that hosts the database.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

OUTPUTS

Microsoft.Azure.Commands.Sql.Backup.Model.AzureSqlDatabaseRestorePointModel

NOTES

----- Example 1: Create a restore point -----

New-AzSqlDatabaseRestorePoint -ResourceGroupName "ResourceGroup01" -ServerName "Server01" -DatabaseName
"Database01" -RestorePointLabel "RestorePoint01"

ResourceGroupName : resourcegroup01
ServerName : server01
DatabaseName : database01
Location : Central US
RestorePointType : DISCRETE
RestorePointCreationDate : 8/12/2015 12:00:00 AM
EarliestRestoreDate :
RestorePointLabel : RestorePoint01

This command creates a restore point for Azure SQL Data Warehouse and returns the details of the restore point.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.sql/new-azsqldatabaserestorepoint>