



## ***Windows PowerShell Get-Help on Cmdlet 'New-AzStaticWebAppUserRoleInvitationLink'***

***PS:\>Get-HELP New-AzStaticWebAppUserRoleInvitationLink -Full***

### NAME

New-AzStaticWebAppUserRoleInvitationLink

### SYNOPSIS

Description for Creates an invitation link for a user with the role

### SYNTAX

```
New-AzStaticWebAppUserRoleInvitationLink -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>]
[-Domain <String>] [-Kind <String>]
    [-NumHoursToExpiration <Int32>] [-Provider <String>] [-Role <String>] [-UserDetail <String>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
    [<CommonParameters>]
```

```
New-AzStaticWebAppUserRoleInvitationLink -InputObject <IWebsitesIdentity> [-Domain <String>] [-Kind <String>]
[-NumHoursToExpiration <Int32>] [-Provider <String>]
    [-Role <String>] [-UserDetail <String>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
```

<Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

## DESCRIPTION

Description for Creates an invitation link for a user with the role

## PARAMETERS

-Name <String>

Name of the static site.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

Name of the resource group to which the resource belongs.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Your Azure subscription ID.

This is a GUID-formatted string (e.g.

00000000-0000-0000-0000-000000000000).

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IWebsitesIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Domain <String>

The domain name for the static site custom domain.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Kind <String>

Kind of resource.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NumHoursToExpiration <Int32>

The number of hours the sas token stays valid

Required? false  
Position? named  
Default value 0  
Accept pipeline input? false  
Accept wildcard characters? false

-Provider <String>

The identity provider for the static site user.

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-Role <String>

The roles for the static site user, in free-form string format

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-UserDetail <String>

The user id for the static site user.

Required? false  
Position? named  
Default value  
Accept pipeline input? false

Accept wildcard characters? false

#### -DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

#### -Proxy <Uri>

The URI for the proxy server to use

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

#### -ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

|                             |       |
|-----------------------------|-------|
| Required?                   | false |
| Position?                   | named |
| Default value               |       |
| Accept pipeline input?      | false |
| Accept wildcard characters? | false |

-Confirm [<SwitchParameter>]

|                             |       |
|-----------------------------|-------|
| Required?                   | false |
| Position?                   | named |
| Default value               |       |
| Accept pipeline input?      | false |
| Accept wildcard characters? | false |

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Websites.Models.IWebsitesIdentity

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Websites.Models.Api20201201.IStaticSiteUserInvitationResponseResource

## NOTES

## COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about\_Hash\_Tables.

INPUTOBJECT <IWebsitesIdentity>: Identity Parameter

[AuthProvider <String>]: The auth provider for the users.

[DomainName <String>]: The custom domain name.

[EnvironmentName <String>]: The stage site identifier.

[FunctionAppName <String>]: Name of the function app registered with the static site build.

[Id <String>]: Resource identity path

[JobHistoryId <String>]: History ID.

[Location <String>]: Location where you plan to create the static site.

[Name <String>]: Name of the static site.

[PrivateEndpointConnectionName <String>]: Name of the private endpoint connection.

[ResourceGroupName <String>]: Name of the resource group to which the resource belongs.

[Slot <String>]: Name of the deployment slot. If a slot is not specified, the API deletes a deployment for the production slot.

[SubscriptionId <String>]: Your Azure subscription ID. This is a GUID-formatted string (e.g. 00000000-0000-0000-0000-000000000000).

[UserId <String>]: The user id of the user.

[WebJobName <String>]: Name of Web Job.

### ----- EXAMPLE 1 -----

```
PS C:\>New-AzStaticWebAppUserRoleInvitationLink -ResourceGroupName azure-rg-test -Name staticweb-pwsh02
-Domain 'xxxxxxxxx.azurestaticapps.net' -Provider 'github'
-UserDetail 'UserName' -Role 'reader' -NumHoursToExpiration 1
```

----- EXAMPLE 2 -----

```
PS C:\>$web = Get-AzStaticWebApp -ResourceGroupName resourceGroup -Name staticweb00
```

```
New-AzStaticWebAppUserRoleInvitationLink -InputObject $web -Domain 'Hostname' -Provider 'github' -UserDetail  
'UserName' -Role 'admin,contributor'  
-NumHoursToExpiration 1
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.websites/new-azstaticwebappuserroleinvitationlink>