



Windows PowerShell Get-Help on Cmdlet 'New-AzWebPubSubCustomCertificate'

PS:\>Get-HELP New-AzWebPubSubCustomCertificate -Full

NAME

New-AzWebPubSubCustomCertificate

SYNOPSIS

Create or update a custom certificate.

SYNTAX

```
New-AzWebPubSubCustomCertificate -Name <String> -ResourceGroupName <String> -ResourceName <String>
[-SubscriptionId <String>] -KeyVaultBaseUri <String>
-KeyVaultSecretName <String> [-KeyVaultSecretVersion <String>] [-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

DESCRIPTION

Create or update a custom certificate.

PARAMETERS

-Name <String>

Custom certificate name

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group that contains the resource.

You can obtain this value from the Azure Resource Manager API or the portal.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceName <String>

The name of the resource.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Gets subscription Id which uniquely identify the Microsoft Azure subscription.

The subscription ID forms part of the URI for every service call.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-KeyVaultBaseUri <String>

Base uri of the KeyVault that stores certificate.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-KeyVaultSecretName <String>

Certificate secret name.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-KeyVaultSecretVersion <String>

Certificate secret version.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.WebPubSub.Models.Api20220801Preview.ICustomCertificate

----- EXAMPLE 1 -----

```
PS C:\>New-AzWebPubSubCustomCertificate -Name mycustomcert -ResourceGroupName rg -ResourceName wps  
-KeyVaultBaseUri https://kvcustomcertificatetest.vault.azure.net/  
-KeyVaultSecretName manual-test
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.signalr/new-azwebpubsubcustomcertificate>