



Windows PowerShell Get-Help on Cmdlet 'New-AzWvdApplication'

PS:\>Get-HELP New-AzWvdApplication -Full

NAME

New-AzWvdApplication

SYNOPSIS

Create or update an application.

SYNTAX

```
New-AzWvdApplication -GroupName <String> -Name <String> -ResourceGroupName <String> -CommandLineSetting
<CommandLineSetting> [-SubscriptionId <String>] [-Description
    <String>] [-FriendlyName <String>] [-ShowInPortal] [-ApplicationType <RemoteApplicationType>]
[-CommandLineArgument <String>] [-FilePath <String>] [-IconIndex
    <Int32>] [-IconPath <String>] [-MsixPackageApplicationId <String>] [-MsixPackageFamilyName <String>] [-DefaultProfile
    <PSObject>] [-Break] [-HttpPipelineAppend
    <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

```
New-AzWvdApplication -GroupName <String> -Name <String> -ResourceGroupName <String> -CommandLineSetting
<CommandLineSetting> [-SubscriptionId <String>] [-Description
```

<String>] [-FriendlyName <String>] [-ShowInPortal] -AppAlias <String> [-DefaultProfile <PSObject>] [-Break]
 [-HttpPipelineAppend <SendAsyncStep[]>]
 [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
 [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Create or update an application.

PARAMETERS

-GroupName <String>

The name of the application group

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of the application within the specified application group

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-CommandLineSetting <CommandLineSetting>

Specifies whether this published application can be launched with command line arguments provided by the client, command line arguments specified at publish time, or no command line arguments at all.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Description <String>

Description of Application.

Required? false
Position? named
Default value
Accept pipeline input? false

Accept wildcard characters? false

-FriendlyName <String>

Friendly name of Application.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ShowInPortal [<SwitchParameter>]

Specifies whether to show the RemoteApp program in the RD Web Access server.

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-AppAlias <String>

App Alias from start menu item

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ApplicationType <RemoteApplicationType>

Resource Type of Application.

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-CommandLineArgument <String>
Command Line Arguments for Application.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-FilePath <String>
Specifies a path for the executable file for the application.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-IconIndex <Int32>
Index of the icon.

Required? false
Position? named
Default value 0
Accept pipeline input? false
Accept wildcard characters? false

-IconPath <String>

Path to icon.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-MsixPackageApplicationId <String>

Specifies the package application Id for MSIX applications

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-MsixPackageFamilyName <String>

Specifies the package family name for MSIX applications

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.DesktopVirtualization.Models.Api20230905.IApplication

----- EXAMPLE 1 -----

PS C:\>New-AzWvdApplication -ResourceGroupName ResourceGroupName `

-GroupName ApplicationGroupName `

-Name ApplicationName `

-FilePath 'C:\windows\system32\mspaint.exe' `

-FriendlyName 'Friendly name' `

-Description 'Description' `

-IconIndex 0 `

-IconPath 'C:\windows\system32\mspaint.exe' `

-CommandLineSetting 'Allow' `

-ShowInPortal:\$true

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.desktopvirtualization/new-azwvdapplication>