



## ***Windows PowerShell Get-Help on Cmdlet 'New-NetAdapterAdvancedProperty'***

***PS:\>Get-HELP New-NetAdapterAdvancedProperty -Full***

### NAME

New-NetAdapterAdvancedProperty

### SYNOPSIS

Creates an advanced property for the network adapter.

### SYNTAX

```
New-NetAdapterAdvancedProperty [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-IncludeHidden]
-InterfaceDescription <String> [-NoRestart] [-RegistryDataType {None
| REG_SZ | REG_DWORD | REG_MULTI_SZ | REG_QWORD}] -RegistryKeyword <String> -RegistryValue <String[]>
[-ThrottleLimit <Int32>] [-WhatIf] [<CommonParameters>]
```

```
New-NetAdapterAdvancedProperty [-Name] <String> [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-IncludeHidden]
[-NoRestart] [-RegistryDataType {None | REG_SZ |
REG_DWORD | REG_MULTI_SZ | REG_QWORD}] -RegistryKeyword <String> -RegistryValue <String[]> [-ThrottleLimit
<Int32>] [-WhatIf] [<CommonParameters>]
```

### DESCRIPTION

The New-NetAdapterAdvancedProperty cmdlet creates an advanced property for the network adapter. The intention is that network adapter manufacturers can use this

cmdlet to manage advanced properties that are not directly supported by Windows Server 2012 and later. This cmdlet is the cmdlet in the network adapter family that

creates a registry key. All other cmdlets read or modify existing registry entries. The use of wildcards in the network adapter identifier, either in the Name or

InterfaceDescription parameters, is not supported.

## PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete. The cmdlet immediately returns an object that

represents the job and then displays the command prompt. You can continue to work in the session while the job completes. To manage the job, use the ``*-Job``

cmdlets. To get the job results, use the Receive-Job (<https://go.microsoft.com/fwlink/?LinkID=113372>) cmdlet. For more information about Windows PowerShell

background jobs, see about\_Jobs (<https://go.microsoft.com/fwlink/?LinkID=113251>).

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession

(<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or

[Get-CimSession](<https://go.microsoft.com/fwlink/p/?LinkId=227966>) cmdlet. The default is the current session on the local computer.

Required? false

Position?                named  
Default value            None  
Accept pipeline input?    False  
Accept wildcard characters? false

**-Confirm [<SwitchParameter>]**

Prompts you for confirmation before running the cmdlet.

Required?                false  
Position?                named  
Default value            False  
Accept pipeline input?    False  
Accept wildcard characters? false

**-IncludeHidden [<SwitchParameter>]**

Indicates that the cmdlet includes both visible and hidden network adapters in the operation. By default only visible network adapters are included. If a wildcard

character is used in identifying a network adapter and this parameter has been specified, then the wildcard string is matched against both hidden and visible network adapters.

Required?                false  
Position?                named  
Default value            False  
Accept pipeline input?    False  
Accept wildcard characters? false

**-InterfaceDescription <String>**

Specifies the network adapter interface description. For a physical network adapter this is typically the name of the vendor of the network adapter followed by a part number and description, such as `Contoso 12345 Gigabit Network Device`.

Required?                true

Position?                named  
Default value            None  
Accept pipeline input?    True (ByPropertyName)  
Accept wildcard characters? false

**-Name <String>**

Specifies the name of the network adapter.

Required?                true  
Position?                0  
Default value            None  
Accept pipeline input?    True (ByPropertyName)  
Accept wildcard characters? false

**-NoRestart [<SwitchParameter>]**

Indicates that the cmdlet does not restart the network adapter after completing the operation. Many advanced properties require restarting the network adapter before the new settings take effect.

Required?                false  
Position?                named  
Default value            False  
Accept pipeline input?    False  
Accept wildcard characters? false

**-RegistryDataType <RegDataType>**

Specifies the type of the value data to be set in the registry. The acceptable values for this parameter are:

- None

- REG\_SZ

- REG\_DWORD

- REG\_QWORD

- REG\_MULTI\_SZ

Required? false  
Position? named  
Default value None  
Accept pipeline input? True (ByPropertyName)  
Accept wildcard characters? false

-RegistryKeyword <String>

Specifies the name of the registry keyword that this cmdlet creates.

Required? true  
Position? named  
Default value None  
Accept pipeline input? True (ByPropertyName)  
Accept wildcard characters? false

-RegistryValue <String[]>

Specifies the value of the advanced property as an array.

Required? true  
Position? named  
Default value None  
Accept pipeline input? True (ByPropertyName)  
Accept wildcard characters? false

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then

Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are

running on the computer. The throttle limit

applies only to the current cmdlet, not to the session or to the computer.

Required?	false
Position?	named
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

#### -WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

#### <CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

None

## OUTPUTS

Microsoft.Management.Infrastructure.CimInstance#ROOT/StandardCimv2/MSFT\_NetAdapterAdvancedPropertySettingData

The `Microsoft.Management.Infrastructure.CimInstance` object is a wrapper class that displays Windows Management

Instrumentation (WMI) objects. The path after the

pound sign (`#`) provides the namespace and class name for the underlying WMI object.

## NOTES

Example 1: Create an advanced property on the specified network adapter

```
PS C:\> New-NetAdapterAdvancedProperty -Name "MyAdapter" -RegistryKeyword "MyKeyword" -RegistryValue "1"
-RegistryDataType REG_SZ
```

This command creates an advanced property on the network adapter named MyAdapter with the registry keyword MyKeyword of type REG\_SZ with the value 1.

Example 2: Create an advanced property on the specified network adapter that does not restart

```
PS C:\> New-NetAdapterAdvancedProperty -Name "MyAdapter" -RegistryKeyword "MyKeyword" -RegistryValue "1"
-RegistryDataType REG_SZ -NoRestart
```

This command creates an advanced property on the network adapter named MyAdapter with the registry keyword MyKeyword of type REG\_SZ with the value 1 and the network

adapter is specified to not restart. Many advanced properties require restarting the network adapter before the new settings take effect.

Example 3: Create an advanced property on the specified network adapter

```
PS C:\> $NetworkAdapter3 = Get-NetAdapter -Name "Ethernet 3"
PS C:\> New-NetAdapterAdvancedProperty -InputObject $NetworkAdapter3 -RegistryKeyword "MyKeyword"
-RegistryValue "1" -RegistryDataType REG_SZ
```

This command is a version of the cmdlet that creates an advanced property on the network adapter named Ethernet 3 using wildcard characters and the pipeline. Use of

wildcard characters is not allowed for the network adapter identifier as part of this cmdlet, but can be used via the pipeline.

```
PS C:\> Get-NetAdapter -Name "Ethernet 3" | New-NetAdapterAdvancedProperty -RegistryKeyword "MyKeyword"
-RegistryValue "1" -RegistryDataType REG_SZ
```

The first command gets the network adapter named Ethernet 3 and stores the result in the variable named \$NetworkAdapter3.

The second command creates an advanced property for the network adapter stored in the \$NetworkAdapter3 variable as registry value 1 for the keyword named MyKeyword.

## RELATED LINKS

Online

Version:

[https://learn.microsoft.com/powershell/module/netadapter/new-netadapteradvancedproperty?view=windowsserver2022-ps&wt.mc\\_id=ps-gethelp](https://learn.microsoft.com/powershell/module/netadapter/new-netadapteradvancedproperty?view=windowsserver2022-ps&wt.mc_id=ps-gethelp)

Get-NetAdapterAdvancedProperty

Remove-NetAdapterAdvancedProperty

Reset-NetAdapterAdvancedProperty

Set-NetAdapterAdvancedProperty