



Windows PowerShell Get-Help on Cmdlet 'Remove-AzAppConfigurationLock'

PS:\>Get-HELP Remove-AzAppConfigurationLock -Full

NAME

Remove-AzAppConfigurationLock

SYNOPSIS

Unlocks a key-value.

SYNTAX

Remove-AzAppConfigurationLock -Endpoint <String> -Key <String> [-Label <String>] [-IfMatch <String>] [-IfNoneMatch <String>] [-SyncToken <String>] [-DefaultProfile

<PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Remove-AzAppConfigurationLock -Endpoint <String> -InputObject <IAppConfigurationdataIdentity> [-Label <String>] [-IfMatch <String>] [-IfNoneMatch <String>]

[-SyncToken <String>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>]

[-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Unlocks a key-value.

PARAMETERS

-Endpoint <String>

The endpoint of the App Configuration instance to send requests to.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Key <String>

The key of the key-value to unlock.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IAppConfigurationdataIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-Label <String>

The label, if any, of the key-value to unlock.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IfMatch <String>

Used to perform an operation only if the targeted resource's etag matches the value provided.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-IfNoneMatch <String>

Used to perform an operation only if the targeted resource's etag does not match the value provided.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SyncToken <String>

Used to guarantee real-time consistency between requests.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

-Confirm [<SwitchParameter>]

Required?	false
Position?	named
Default value	
Accept pipeline input?	false
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.AppConfigurationdata.Models.IAppConfigurationdataIdentity

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.AppConfigurationdata.Models.IKeyValue

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IAppConfigurationdataIdentity>: Identity Parameter

[Id <String>]: Resource identity path

[Key <String>]: The key of the key-value to retrieve.

----- EXAMPLE 1 -----

```
PS C:\>Remove-AzAppConfigurationLock -Endpoint $endpoint -Key keyName1
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.appconfiguration/remove-azappconfigurationlock>