



Windows PowerShell Get-Help on Cmdlet 'Remove-AzApplicationGatewayBackendSetting'

PS:\>Get-HELP Remove-AzApplicationGatewayBackendSetting -Full

WARNING: The names of some imported commands from the module 'Microsoft.Azure.PowerShell.Cmdlets.Network' include unapproved verbs that might make them less discoverable.

To find the commands with unapproved verbs, run the Import-Module command again with the Verbose parameter. For a list of approved verbs, type Get-Verb.

NAME

Remove-AzApplicationGatewayBackendSetting

SYNOPSIS

Removes back-end TCP/TLS settings from an application gateway.

SYNTAX

Remove-AzApplicationGatewayBackendSetting -ApplicationGateway

<Microsoft.Azure.Commands.Network.Models.PSApplicationGateway> [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Name

<System.String> [<CommonParameters>]

DESCRIPTION

The Remove-AzApplicationGatewayBackendSetting cmdlet removes back-end TCP/TLS settings from Page 14

application gateway.

PARAMETERS

-ApplicationGateway <Microsoft.Azure.Commands.Network.Models.PSApplicationGateway>

The applicationGateway

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

The name of the backend settings

Required? true

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.Commands.Network.Models.PSApplicationGateway

OUTPUTS

Microsoft.Azure.Commands.Network.Models.PSApplicationGateway

NOTES

Example 1: Remove back-end TCP\TLS settings from an application gateway

```
$AppGw = Get-AzApplicationGateway -Name "ApplicationGateway01" -ResourceGroupName "ResourceGroup01"  
Remove-AzApplicationGatewayBackendSetting -ApplicationGateway $AppGw -Name "BackEndSetting02"  
Set-AzApplicationGateway -ApplicationGateway $AppGW
```

The first command gets an application gateway named ApplicationGateway01 that belongs to the resource group named ResourceGroup01 and stores it in the \$AppGw variable. The second command removes the back-end TCP\TLS setting named BackEndSetting02 from the application gateway stored in \$AppGw. Finally, the third command updates the application gateway.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.network/remove-azapplicationgatewaybackendsetting>

`Add-AzApplicationGatewayBackendSetting`

`New-AzApplicationGatewayBackendSetting`

`Get-AzApplicationGatewayBackendSetting`

`Set-AzApplicationGatewayBackendSetting`