



## ***Windows PowerShell Get-Help on Cmdlet 'Remove-AzContainerRegistryExportPipeline'***

***PS:\>Get-HELP Remove-AzContainerRegistryExportPipeline -Full***

### NAME

Remove-AzContainerRegistryExportPipeline

### SYNOPSIS

Deletes an export pipeline from a container registry.

### SYNTAX

Remove-AzContainerRegistryExportPipeline -Name <String> -RegistryName <String> -ResourceGroupName <String>  
[-SubscriptionId <String>] [-DefaultProfile <PSObject>]

[-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait]  
[-PassThru] [-Proxy <Uri>] [-ProxyCredential  
<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Remove-AzContainerRegistryExportPipeline -InputObject <IContainerRegistryIdentity> [-DefaultProfile <PSObject>]  
[-AsJob] [-Break] [-HttpPipelineAppend  
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-PassThru] [-Proxy <Uri>] [-ProxyCredential  
<PSCredential>] [-ProxyUseDefaultCredentials]  
[-WhatIf] [-Confirm] [<CommonParameters>]

## DESCRIPTION

Deletes an export pipeline from a container registry.

## PARAMETERS

-Name <String>

The name of the export pipeline.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-RegistryName <String>

The name of the container registry.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

The value must be an UUID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IContainerRegistryIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-AsJob [<SwitchParameter>]

Run the command as a job

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-PassThru [<SwitchParameter>]

Returns true when the command succeeds

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### <CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see

about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.ContainerRegistry.Models.IContainerRegistryIdentity

## OUTPUTS

System.Boolean

## NOTES

### COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about\_Hash\_Tables.

INPUTOBJECT <IContainerRegistryIdentity>: Identity Parameter

[AgentPoolName <String>]: The name of the agent pool.

[CacheRuleName <String>]: The name of the cache rule.

[ConnectedRegistryName <String>]: The name of the connected registry.

[CredentialSetName <String>]: The name of the credential set.

[ExportPipelineName <String>]: The name of the export pipeline.

[GroupName <String>]: The name of the private link resource.

[Id <String>]: Resource identity path

[ImportPipelineName <String>]: The name of the import pipeline.

[PipelineRunName <String>]: The name of the pipeline run.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection.

[RegistryName <String>]: The name of the container registry.

[ReplicationName <String>]: The name of the replication.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[RunId <String>]: The run ID.

[ScopeMapName <String>]: The name of the scope map.

[SubscriptionId <String>]: The ID of the target subscription. The value must be an UUID.

[TaskName <String>]: The name of the container registry task.

[TaskRunName <String>]: The name of the task run.

[TokenName <String>]: The name of the token.

[WebhookName <String>]: The name of the webhook.

----- EXAMPLE 1 -----

```
PS C:\>Remove-AzContainerRegistryExportPipeline -name Exam -RegistryName RegistryExample  
-ResourceGroupName MyResourceGroup
```

## RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.containerregistry/remove-azcontainerregistryexportpipeline>