



Windows PowerShell Get-Help on Cmdlet 'Remove-AzDataLakeAnalyticsCatalogCredential'

PS:\>Get-HELP Remove-AzDataLakeAnalyticsCatalogCredential -Full

NAME

Remove-AzDataLakeAnalyticsCatalogCredential

SYNOPSIS

Deletes an Azure Data Lake Analytics credential.

SYNTAX

```
Remove-AzDataLakeAnalyticsCatalogCredential [-Account] <System.String> [-DatabaseName] <System.String> [-Name]
<System.String> [[-Password]
                                     <System.Management.Automation.PSCredential>] [-DefaultProfile
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force]
[-PassThru] [-Recurse] [-Confirm] [-WhatIf] [<CommonParameters>]
```

DESCRIPTION

The Remove-AzDataLakeAnalyticsCatalogCredential cmdlet deletes an Azure Data Lake Analytics catalog credential.

-Account <System.String>

Specifies the Data Lake Analytics account name.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DatabaseName <System.String>

Specifies the name of the database that holds the credential.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Force <System.Management.Automation.SwitchParameter>

Forces the command to run without asking for user confirmation.

Required? false

Position? named

Default value False

Accept pipeline input? False
Accept wildcard characters? false

-Name <System.String>

Specifies the name of the credential.

Required? true
Position? 2
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-PassThru <System.Management.Automation.SwitchParameter>

Indicates that this cmdlet does not wait for the operation to complete. Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-Password <System.Management.Automation.PSCredential>

The password for the credential. This is required if the caller is not the owner of the account.

Required? false
Position? 3
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Recurse <System.Management.Automation.SwitchParameter>

Indicates that this delete operation should go through and also delete and drop all resources dependent on this credential.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	True (ByPropertyName)
Accept wildcard characters?	false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-WhatIf <System.Management.Automation.SwitchParameter>

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

System.Management.Automation.PSCredential

System.Management.Automation.SwitchParameter

OUTPUTS

System.Boolean

NOTES

----- Example 1: Remove a credential -----

```
Remove-AzDataLakeAnalyticsCatalogCredential -AccountName "ContosoAdla" `
    -DatabaseName "DatabaseName" `
    -Name "CredName"
```

This command removes the specified Data Lake Analytics catalog credential.

RELATED LINKS

