



## ***Windows PowerShell Get-Help on Cmdlet 'Remove-AzDataLakeAnalyticsDataSource'***

***PS:\>Get-HELP Remove-AzDataLakeAnalyticsDataSource -Full***

### NAME

Remove-AzDataLakeAnalyticsDataSource

### SYNOPSIS

Removes a data source from a Data Lake Analytics account.

### SYNTAX

```
Remove-AzDataLakeAnalyticsDataSource [-Account] <System.String> [-Blob] <System.String> [[-Force]] [[-PassThru]]
[[ -ResourceGroupName] <System.String>]
[-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
[-Confirm] [-WhatIf] [<CommonParameters>]
```

```
Remove-AzDataLakeAnalyticsDataSource [-Account] <System.String> [-DataLakeStore] <System.String> [[-Force]]
[[ -PassThru]] [[ -ResourceGroupName] <System.String>]
[-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
[-Confirm] [-WhatIf] [<CommonParameters>]
```

### DESCRIPTION

The Remove-AzDataLakeAnalyticsDataSource cmdlet removes a data source from an Azure Data Lake Analytics account.

## PARAMETERS

-Account <System.String>

Specifies the Data Lake Analytics account name.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Blob <System.String>

Specifies the name of the AzureBlob Storage account to remove.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DataLakeStore <System.String>

Specifies the name of the AzureData Lake Store account to remove.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure

|                             |       |
|-----------------------------|-------|
| Required?                   | false |
| Position?                   | named |
| Default value               | None  |
| Accept pipeline input?      | False |
| Accept wildcard characters? | false |

-Force <System.Management.Automation.SwitchParameter>

Forces the command to run without asking for user confirmation.

|                             |       |
|-----------------------------|-------|
| Required?                   | false |
| Position?                   | 2     |
| Default value               | False |
| Accept pipeline input?      | False |
| Accept wildcard characters? | false |

-PassThru <System.Management.Automation.SwitchParameter>

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

|                             |       |
|-----------------------------|-------|
| Required?                   | false |
| Position?                   | 3     |
| Default value               | False |
| Accept pipeline input?      | False |
| Accept wildcard characters? | false |

-ResourceGroupName <System.String>

Specifies the resource group name of the Data Lake Analytics account.

|               |       |
|---------------|-------|
| Required?     | false |
| Position?     | 4     |
| Default value | None  |

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

#### -Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

#### -WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

#### <CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

System.String

## OUTPUTS

## NOTES

----- Example 1: Remove a data source -----

```
Remove-AzDataLakeAnalyticsDataSource -Account "ContosoAdlAccount" -Blob "AzureStorage01"
```

This command removes the data source named AzureStorage01 from the account named ContosoAdlAccount.

## RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.datalakeanalytics/remove-azdatalakeanalyticsdatasource>

Add-AzDataLakeAnalyticsDataSource

Set-AzDataLakeAnalyticsDataSource