



Windows PowerShell Get-Help on Cmdlet 'Remove-AzDevCenterAdminEnvironmentType'

PS:\>Get-HELP Remove-AzDevCenterAdminEnvironmentType -Full

WARNING: The names of some imported commands from the module 'Az.DevCenterdata.custom' include unapproved verbs that might make them less discoverable. To find the commands with unapproved verbs, run the Import-Module command again with the Verbose parameter. For a list of approved verbs, type Get-Verb.

NAME

Remove-AzDevCenterAdminEnvironmentType

SYNOPSIS

Deletes an environment type.

SYNTAX

```
Remove-AzDevCenterAdminEnvironmentType -DevCenterName <String> -Name <String> -ResourceGroupName  
<String> [-SubscriptionId <String>] [-DefaultProfile <PSObject>]  
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-PassThru] [-Proxy  
<Uri>] [-ProxyCredential <PSCredential>]  
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Remove-AzDevCenterAdminEnvironmentType -InputObject <IDevCenterIdentity> [-DefaultProfile <PSObject>] [-Break]  
[-HttpPipelineAppend <SendAsyncStep[]>]
```

[-HttpPipelinePrepend <SendAsyncStep[]>] [-PassThru] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]

DESCRIPTION

Deletes an environment type.

PARAMETERS

-DevCenterName <String>

The name of the devcenter.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of the environment type.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IDevCenterIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-PassThru [<SwitchParameter>]

Returns true when the command succeeds

Required? false

Position? named

Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.DevCenter.Models.IDevCenterIdentity

OUTPUTS

System.Boolean

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

INPUTOBJECT <IDevCenterIdentity>: Identity Parameter

[AttachedNetworkConnectionName <String>]: The name of the attached NetworkConnection.

[CatalogName <String>]: The name of the Catalog.

[DevBoxDefinitionName <String>]: The name of the Dev Box definition.

[DevCenterName <String>]: The name of the devcenter.

[EnvironmentDefinitionName <String>]: The name of the Environment Definition.

[EnvironmentTypeName <String>]: The name of the environment type.

[GalleryName <String>]: The name of the gallery.

[Id <String>]: Resource identity path

[ImageName <String>]: The name of the image.

[Location <String>]: The Azure region

[NetworkConnectionName <String>]: Name of the Network Connection that can be applied to a Pool.

[OperationId <String>]: The ID of an ongoing async operation

[PoolName <String>]: Name of the pool.

[ProjectName <String>]: The name of the project.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[ScheduleName <String>]: The name of the schedule that uniquely identifies it.

[SubscriptionId <String>]: The ID of the target subscription.

[TaskName <String>]: The name of the Task.

[VersionName <String>]: The version of the image.

----- EXAMPLE 1 -----

```
PS C:\>Remove-AzDevCenterAdminEnvironmentType -ResourceGroupName testRg -DevCenterName Contoso -Name
DevTest
```

----- EXAMPLE 2 -----

```
PS C:\>$envType = Get-AzDevCenterAdminEnvironmentType -ResourceGroupName testRg -DevCenterName Contoso  
-Name DevTest
```

```
Remove-AzDevCenterAdminEnvironmentType -InputObject $envType
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.devcenter/remove-azdevcenteradminenvironmenttype>