



Windows PowerShell Get-Help on Cmdlet 'Remove-AzDiskEncryptionSet'

PS:\>Get-HELP Remove-AzDiskEncryptionSet -Full

NAME

Remove-AzDiskEncryptionSet

SYNOPSIS

Removes a disk encryption set.

SYNTAX

```

Remove-AzDiskEncryptionSet [-InputObject] [-InputObject]

<Microsoft.Azure.Commands.Compute.Automation.Models.PSDiskEncryptionSet> [-AsJob] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force] [-Confirm]
[-WhatIf] [<CommonParameters>]

Remove-AzDiskEncryptionSet [-ResourceGroupName] <System.String> [-Name] <System.String> [-AsJob]
[-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force] [-Confirm]
[-WhatIf] [<CommonParameters>]

Remove-AzDiskEncryptionSet [-ResourceId] <System.String> [-AsJob] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force] [-Confirm]
[-WhatIf] [<CommonParameters>]

```

[-WhatIf] [<CommonParameters>]

DESCRIPTION

Removes a disk encryption set.

PARAMETERS

-AsJob <System.Management.Automation.SwitchParameter>

Run cmdlet in the background

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Force <System.Management.Automation.SwitchParameter>

Forces the command to run without asking for user confirmation.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.Compute.Automation.Models.PSDiskEncryptionSet>

The local object of the disk encryption set.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-Name <System.String>

Name of disk encryption set.

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ResourceGroupName <System.String>

Specifies the name of a resource group.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ResourceId <System.String>

The ID of the resource.

Required? true

Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

System.String

Microsoft.Azure.Commands.Compute.Automation.Models.PSDiskEncryptionSet

OUTPUTS

Microsoft.Azure.Commands.Compute.Automation.Models.PSOperationStatusResponse

NOTES

----- Example 1 -----

```
Remove-AzDiskEncryptionSet -ResourceGroupName 'rg1' -Name 'enc1' -Force;
```

Delete disk encryption set 'enc1' in 'rg1'

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.compute/remove-azdiskencryptionset>