



Windows PowerShell Get-Help on Cmdlet 'Remove-AzDnsForwardingRulesetVirtualNetworkLink'

PS:\>Get-HELP Remove-AzDnsForwardingRulesetVirtualNetworkLink -Full

NAME

Remove-AzDnsForwardingRulesetVirtualNetworkLink

SYNOPSIS

Deletes a virtual network link to a DNS forwarding ruleset.

WARNING: This operation cannot be undone.

SYNTAX

```
Remove-AzDnsForwardingRulesetVirtualNetworkLink -DnsForwardingRulesetName <String> -Name <String>
-ResourceGroupName <String> [-SubscriptionId <String>] [-IfMatch
<String>] [-DefaultProfile <PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-NoWait] [-PassThru]
[-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

```
Remove-AzDnsForwardingRulesetVirtualNetworkLink -InputObject <IDnsResolverIdentity> [-IfMatch <String>]
[-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-PassThru] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>]
```

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

DESCRIPTION

Deletes a virtual network link to a DNS forwarding ruleset.

WARNING: This operation cannot be undone.

PARAMETERS

-DnsForwardingRulesetName <String>

The name of the DNS forwarding ruleset.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of the virtual network link.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IDnsResolverIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-IfMatch <String>

ETag of the resource.

Omit this value to always overwrite the current resource.

Specify the last-seen ETag value to prevent accidentally overwriting any concurrent changes.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-DefaultProfile <PSObject>`

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-AsJob [<SwitchParameter>]`

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

`-Break [<SwitchParameter>]`

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

`-HttpPipelineAppend <SendAsyncStep[]>`

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-PassThru [<SwitchParameter>]

Returns true when the command succeeds

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.DnsResolver.Models.IDnsResolverIdentity

OUTPUTS

System.Boolean

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run `Get-Help about_Hash_Tables`.

INPUTOBJECT <IDnsResolverIdentity>: Identity Parameter

[DnsForwardingRulesetName <String>]: The name of the DNS forwarding ruleset.

[DnsResolverName <String>]: The name of the DNS resolver.

[ForwardingRuleName <String>]: The name of the forwarding rule.

[Id <String>]: Resource identity path

[InboundEndpointName <String>]: The name of the inbound endpoint for the DNS resolver.

[OutboundEndpointName <String>]: The name of the outbound endpoint for the DNS resolver.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

[VirtualNetworkLinkName <String>]: The name of the virtual network link.

[VirtualNetworkName <String>]: The name of the virtual network.

----- EXAMPLE 1 -----

```
PS C:\>Remove-AzDnsForwardingRulesetVirtualNetworkLink -DnsForwardingRulesetName dnsForwardingRuleset
-Name sampleVnetLink -ResourceGroupName sampleRG
```

----- EXAMPLE 2 -----

```
PS C:\>$inputObject = Get-AzDnsForwardingRulesetVirtualNetworkLink -DnsForwardingRulesetName
pstestdnsresolvername -Name samplevnetLink1 -ResourceGroupName
powershell-test-rg
```

```
Remove-AzDnsForwardingRulesetVirtualNetworkLink -InputObject $inputObject
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.dnsresolver/remove-azdnsforwardingrulesetvirtualnetworklink>