



Windows PowerShell Get-Help on Cmdlet 'Remove-AzElasticSanVolumeGroup'

PS:\>Get-HELP Remove-AzElasticSanVolumeGroup -Full

NAME

Remove-AzElasticSanVolumeGroup

SYNOPSIS

Delete an VolumeGroup.

SYNTAX

```
Remove-AzElasticSanVolumeGroup -ElasticSanName <String> -Name <String> -ResourceGroupName <String>
[-SubscriptionId <String>] [-DefaultProfile <PSObject>] [-AsJob]

[-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-PassThru]
[-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Remove-AzElasticSanVolumeGroup -Name <String> -ElasticSanInputObject <IElasticSanIdentity> [-DefaultProfile
<PSObject>] [-AsJob] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-PassThru] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]

[-WhatIf] [-Confirm] [<CommonParameters>]
```

Remove-AzElasticSanVolumeGroup -InputObject <IElasticSanIdentity> [-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-PassThru] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]

DESCRIPTION

Delete an VolumeGroup.

PARAMETERS

-ElasticSanName <String>

The name of the ElasticSan.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of the VolumeGroup.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-InputObject <IElasticSanIdentity>

Identity Parameter

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

-ElasticSanInputObject <IElasticSanIdentity>

Identity Parameter

Required? true
Position? named
Default value
Accept pipeline input? true (ByValue)
Accept wildcard characters? false

`-DefaultProfile <PSObject>`

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-AsJob [<SwitchParameter>]`

Run the command as a job

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

`-Break [<SwitchParameter>]`

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

`-HttpPipelineAppend <SendAsyncStep[]>`

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-PassThru [<SwitchParameter>]

Returns true when the command succeeds

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.ElasticSan.Models.IElasticSanIdentity

OUTPUTS

System.Boolean

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

[ElasticSanName <String>]: The name of the ElasticSan.

[Id <String>]: Resource identity path

[PrivateEndpointConnectionName <String>]: The name of the Private Endpoint connection.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SnapshotName <String>]: The name of the volume snapshot within the given volume group.

[SubscriptionId <String>]: The ID of the target subscription.

[VolumeGroupName <String>]: The name of the VolumeGroup.

[VolumeName <String>]: The name of the Volume.

INPUTOBJECT <IElasticSanIdentity>: Identity Parameter

[ElasticSanName <String>]: The name of the ElasticSan.

[Id <String>]: Resource identity path

[PrivateEndpointConnectionName <String>]: The name of the Private Endpoint connection.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SnapshotName <String>]: The name of the volume snapshot within the given volume group.

[SubscriptionId <String>]: The ID of the target subscription.

[VolumeGroupName <String>]: The name of the VolumeGroup.

[VolumeName <String>]: The name of the Volume.

----- EXAMPLE 1 -----

```
PS C:\>Remove-AzElasticSanVolumeGroup -ResourceGroupName myresourcegroup -ElasticSanName myelasticsan  
-Name myvolumegroup
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.elasticsan/remove-azelasticsanvolumegroup>

