



Windows PowerShell Get-Help on Cmdlet 'Remove-AzKeyVault'

PS:\>Get-HELP Remove-AzKeyVault -Full

NAME

Remove-AzKeyVault

SYNOPSIS

Deletes a key vault.

SYNTAX

```
Remove-AzKeyVault [-InputObject] <Microsoft.Azure.Commands.KeyVault.Models.PSKeyVault> [-AsJob] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force] [-PassThru]
[-SubscriptionId <System.String>] [-Confirm] [-WhatIf]
    [<CommonParameters>]
```

```
Remove-AzKeyVault [-InputObject] <Microsoft.Azure.Commands.KeyVault.Models.PSKeyVault> [-AsJob] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force]
-InRemovedState [-PassThru] [-SubscriptionId <System.String>]
    [-Confirm] [-WhatIf] [<CommonParameters>]
```

```
Remove-AzKeyVault [-VaultName] <System.String> [-Location] <System.String> [-AsJob] [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force]
```

-InRemovedState [-PassThru] [-SubscriptionId <System.String>]

[-Confirm] [-WhatIf] [<CommonParameters>]

Remove-AzKeyVault [-ResourceId] <System.String> [-Location] <System.String> [-AsJob] [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force]

-InRemovedState [-PassThru] [-SubscriptionId <System.String>]

[-Confirm] [-WhatIf] [<CommonParameters>]

Remove-AzKeyVault [-VaultName] <System.String> [[-ResourceGroupName] <System.String>] [[-Location]

<System.String>] [-AsJob] [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force] [-PassThru]

[-SubscriptionId <System.String>] [-Confirm] [-WhatIf]

[<CommonParameters>]

Remove-AzKeyVault [-ResourceId] <System.String> [[-Location] <System.String>] [-AsJob] [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Force] [-PassThru]

[-SubscriptionId <System.String>] [-Confirm] [-WhatIf]

[<CommonParameters>]

DESCRIPTION

The Remove-AzKeyVault cmdlet deletes the specified key vault. It also deletes all keys and secrets contained in that instance. Note that although specifying the

resource group is optional for this cmdlet, you should so for better performance.

PARAMETERS

-AsJob <System.Management.Automation.SwitchParameter>

Run cmdlet in the background

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Force <System.Management.Automation.SwitchParameter>

Indicates that the cmdlet does not prompt you for confirmation. By default, this cmdlet prompts you to confirm that you want to delete the key vault.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.KeyVault.Models.PSKeyVault>

Key Vault object to be deleted.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-InRemovedState <System.Management.Automation.SwitchParameter>

Remove the previously deleted vault permanently.

Required?	true
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-Location <System.String>

The location of the deleted vault.

Required?	false
Position?	2
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-PassThru <System.Management.Automation.SwitchParameter>

This Cmdlet does not return an object by default. If this switch is specified, it returns true if successful.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-ResourceGroupName <System.String>

Specifies the name of a resource group.

Required?	false
Position?	1
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-ResourceId <System.String>

KeyVault Resource Id.

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-SubscriptionId <System.String>

The ID of the subscription. By default, cmdlets are executed in the subscription that is set in the current context. If the user specifies another subscription,

the current cmdlet is executed in the subscription specified by the user. Overriding subscriptions only take effect during the lifecycle of the current cmdlet. It

does not change the subscription in the context, and does not affect subsequent cmdlets.

Required? false

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-VaultName <System.String>

Specifies the name of the key vault to remove.

Required? true

Position? 0

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run. Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.Commands.KeyVault.Models.PSKeyVault

System.String

OUTPUTS

NOTES

----- Example 1: Remove a key vault -----

```
Remove-AzKeyVault -VaultName "Contoso03Vault" -PassThru
```

True

This command removes the key vault named Contoso03Vault from your current subscription.

Example 2: Remove a key vault from a specified resource group

```
Remove-AzKeyVault -Name "Contoso03Vault" -ResourceGroupName "Group14" -PassThru
```

True

This command removes the key vault named Contoso03Vault from the named resource group. If you do not specify the resource group name, the cmdlet searches for the named key vault to delete in your current subscription.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.keyvault/remove-azkeyvault>

Get-AzKeyVault

