



Windows PowerShell Get-Help on Cmdlet 'Remove-AzServiceFabricSetting'

PS:\>Get-HELP Remove-AzServiceFabricSetting -Full

NAME

Remove-AzServiceFabricSetting

SYNOPSIS

Remove one or multiple Service Fabric setting from the cluster.

SYNTAX

```
Remove-AzServiceFabricSetting [-ResourceGroupName] <System.String> [-Name] <System.String> [-DefaultProfile  
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -Parameter  
<System.String> -Section <System.String> [-Confirm] [-WhatIf]  
[<CommonParameters>]
```

```
Remove-AzServiceFabricSetting [-ResourceGroupName] <System.String> [-Name] <System.String> [-DefaultProfile  
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>  
-SettingsSectionDescription  
    <Microsoft.Azure.Commands.ServiceFabric.Models.PSSettingsSectionDescription[]> [-Confirm] [-WhatIf]  
[<CommonParameters>]
```

DESCRIPTION

Use Remove-AzServiceFabricSetting to remove Service Fabric settings from the cluster.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

Specify the name of the cluster

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Parameter <System.String>

Parameter name of the fabric setting

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-ResourceGroupName <System.String>

Specify the name of the resource group.

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Section <System.String>

Section name of the fabric setting

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-SettingsSectionDescription <Microsoft.Azure.Commands.ServiceFabric.Models.PSSettingsSectionDescription[]>

An array of fabric settings

Required? true
Position? named
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False

Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

Microsoft.Azure.Commands.ServiceFabric.Models.PSSettingsSectionDescription[]

OUTPUTS

Microsoft.Azure.Commands.ServiceFabric.Models.PSCluster

NOTES

----- Example 1 -----

```
Remove-AzServiceFabricSetting -ResourceGroupName 'Group1' -Name 'Contoso01SFCluster' -Section 'EseStore'  
-Parameter 'MaxCursors'
```

This command will remove settings 'MaxCursors' under 'EseStore' section.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.servicefabric/remove-azservicefabricsetting>