



## ***Windows PowerShell Get-Help on Cmdlet 'Remove-AzStreamAnalyticsInput'***

***PS:\>Get-HELP Remove-AzStreamAnalyticsInput -Full***

### NAME

Remove-AzStreamAnalyticsInput

### SYNOPSIS

Deletes an input from the streaming job.

### SYNTAX

Remove-AzStreamAnalyticsInput -JobName <String> -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] [-DefaultProfile <PSObject>] [-Break]

[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-PassThru] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]

[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

Remove-AzStreamAnalyticsInput -InputObject <IStreamAnalyticsIdentity> [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]

[-HttpPipelinePrepend <SendAsyncStep[]>] [-PassThru] [-Proxy <Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]

[<CommonParameters>]

## DESCRIPTION

Deletes an input from the streaming job.

## PARAMETERS

-JobName <String>

The name of the streaming job.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Name <String>

The name of the input.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IStreamAnalyticsIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

**-HttpPipelineAppend <SendAsyncStep[]>**

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

**-HttpPipelinePrepend <SendAsyncStep[]>**

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

**-PassThru [<SwitchParameter>]**

Returns true when the command succeeds

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

#### -Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.StreamAnalytics.Models.IStreamAnalyticsIdentity

## OUTPUTS

System.Boolean

## NOTES

### COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about\_Hash\_Tables.

INPUTOBJECT <IStreamAnalyticsIdentity>: Identity Parameter

[ClusterName <String>]: The name of the cluster.

[FunctionName <String>]: The name of the function.

[Id <String>]: Resource identity path

[InputName <String>]: The name of the input.

[JobName <String>]: The name of the streaming job.

[Location <String>]: The region in which to retrieve the subscription's quota information. You can find out which regions Azure Stream Analytics is supported in

here: <https://azure.microsoft.com/en-us/regions/>

[OutputName <String>]: The name of the output.

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[SubscriptionId <String>]: The ID of the target subscription.

[TransformationName <String>]: The name of the transformation.

#### ----- EXAMPLE 1 -----

```
PS C:\>Remove-AzStreamAnalyticsInput -ResourceGroupName azure-rg-test -JobName sajob-01-pwsh -Name input-01
```

#### ----- EXAMPLE 2 -----

```
PS C:\>Get-AzStreamAnalyticsInput -ResourceGroupName azure-rg-test -JobName sajob-02-pwsh -Name input-01 |  
Remove-AzStreamAnalyticsInput
```

## RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.streamanalytics/remove-azstreamanalyticsinput>