



## ***Windows PowerShell Get-Help on Cmdlet 'Remove-AzWvdWorkspace'***

***PS:\>Get-HELP Remove-AzWvdWorkspace -Full***

### **NAME**

Remove-AzWvdWorkspace

### **SYNOPSIS**

Remove a workspace.

### **SYNTAX**

```
Remove-AzWvdWorkspace -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] [-DefaultProfile
<PSObject>] [-Break] [-HttpPipelineAppend
<SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-PassThru] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf]
[-Confirm] [<CommonParameters>]
```

```
Remove-AzWvdWorkspace -InputObject <IDesktopVirtualizationIdentity> [-DefaultProfile <PSObject>] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-PassThru] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]
[<CommonParameters>]
```

## DESCRIPTION

Remove a workspace.

## PARAMETERS

-Name <String>

The name of the workspace

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IDesktopVirtualizationIdentity>

Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

#### -HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

#### -PassThru [<SwitchParameter>]

Returns true when the command succeeds

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

#### -Proxy <Uri>

The URI for the proxy server to use

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

#### -ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

## <CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about\\_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.DesktopVirtualization.Models.IDesktopVirtualizationIdentity

## OUTPUTS

System.Boolean

## NOTES

### COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

[about\\_Hash\\_Tables](#).

INPUTOBJECT <IDesktopVirtualizationIdentity>: Identity Parameter

[ApplicationGroupName <String>]: The name of the application group

[ApplicationName <String>]: The name of the application within the specified application group

[DesktopName <String>]: The name of the desktop within the specified desktop group

[HostPoolName <String>]: The name of the host pool within the specified resource group

[Id <String>]: Resource identity path

[MsixPackageFullName <String>]: The version specific package full name of the MSIX package within specified hostpool

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection associated with the Azure

## resource

[ResourceGroupName <String>]: The name of the resource group. The name is case insensitive.

[ScalingPlanName <String>]: The name of the scaling plan.

[ScalingPlanScheduleName <String>]: The name of the ScalingPlanSchedule

[SessionHostName <String>]: The name of the session host within the specified host pool

[SubscriptionId <String>]: The ID of the target subscription.

[UserSessionId <String>]: The name of the user session within the specified session host

[WorkspaceName <String>]: The name of the workspace

### ----- EXAMPLE 1 -----

```
PS C:\>Remove-AzWvdWorkspace -ResourceGroupName ResourceGroupName -Name WorkspaceName
```

## RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.desktopvirtualization/remove-azwvdworkspace>