



Windows PowerShell Get-Help on Cmdlet 'Remove-SFTPItem'

PS:\>Get-HELP Remove-SFTPItem -Full

NAME

Remove-SFTPItem

SYNOPSIS

Deletes the specified item on a SFTP session.

SYNTAX

Remove-SFTPItem [-SessionId] <Int32[]> [-Path] <String> [-Force] [<CommonParameters>]

Remove-SFTPItem [-SFTPSession] <SftpSession[]> [-Path] <String> [-Force] [<CommonParameters>]

DESCRIPTION

Deletes the specified item on a SFTP session.

PARAMETERS

-SessionId <Int32[]>

SFTP Session Id of an exiting session.

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Path <String>

Path of item to be removed on remote host.

Required? true
Position? 1
Default value None
Accept pipeline input? False
Accept wildcard characters? false

-Force [<SwitchParameter>]

Force the deletion of a none empty directory by recursively deleting all files in it.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-SFTPSession <SftpSession[]>

SFTP Session Object of an exiting session.

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

System.Int32[]

SSH.SftpSession[]

OUTPUTS

NOTES

----- Example 1 -----

```
PS C:\> Remove-SFTPItem -SessionId 0 -Path /tmp/example.txt
```

Remove /tmp/example.txt in sftp session 0

RELATED LINKS

Online Version: <https://github.com/darkoperator/Posh-SSH/tree/master/docs>