



python



PowerShell

FPDF Library

PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Repair-AppvClientConnectionGroup'

PS C:\Users\wahid> Get-Help Repair-AppvClientConnectionGroup

NAME

Repair-AppvClientConnectionGroup

SYNOPSIS

Resets the user package settings for the connection group.

SYNTAX

Repair-AppvClientConnectionGroup [-ConnectionGroup]

<AppvClientConnectionGroup> [-Extensions] [-Global] [-UserState]

[<CommonParameters>]

Repair-AppvClientConnectionGroup [-GroupId] <Guid> [-VersionId] <Guid>

[-Extensions] [-Global] [-UserState] [<CommonParameters>]

Repair-AppvClientConnectionGroup [-Name] <String> [-Extensions] [-Global]

[-UserState] [<CommonParameters>]

DESCRIPTION

The Repair-AppvClientConnectionGroup cmdlet resets the user settings of the

connection group. Resetting the settings causes permanent loss of any user-specific application settings in the package. The settings are reset to their original state when the connection group was originally added to the system.

PARAMETERS

-ConnectionGroup <AppvClientConnectionGroup>

Specifies an App-V Connection Group object.

-Extensions [<SwitchParameter>]

Indicates that the cmdlet repairs the extension points of a connection group only, and does not delete the user state of the connection group.

-Global [<SwitchParameter>]

Indicates that this cmdlet resets user settings for the specified packages for all users on the computer. Usage of the Global parameter requires administrative credentials.

-GroupId <Guid>

Specifies the group ID of specific connection group.

-Name <String>

Specifies the name of the Microsoft Application Virtualization (App-V) Connection Group.

-UserState [<SwitchParameter>]

Indicates that the cmdlet deletes the user state of the connection group only, and does not perform a repair on the extension points.

-VersionId <Guid>

Specifies a GUID that differentiates a connection group version from other versions, whether older, newer, or of a different lineage. If you do not

specify this parameter, the cmdlet operates on all versions of the connection group.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

----- Example 1: Repair a named connection group -----

```
PS C:\> Repair-AppvClientConnectionGroup -Name "MyGroup"
```

This command repairs the connection group named MyGroup.

----- Example 2: Repair a connection group by using its ID -----

```
PS C:\> Repair-AppvClientConnectionGroup -GroupID  
793afd37-bd68-4ea1-859a-669f6afd0aa8
```

This command repairs the connection group that has the group ID 793afd37-bd68-4ea1-859a-669f6afd0aa8.

Example 3: Repair all connection groups that have names that match a string

```
PS C:\> Get-AppvClientConnectionGroup -Name "MyGr*" |  
Repair-AppvClientConnectionGroup
```

This command finds all of the connection groups that have the string MyGr in the name, and then repairs them.

REMARKS

To see the examples, type: "get-help Repair-AppvClientConnectionGroup -examples".

For more information, type: "get-help Repair-AppvClientConnectionGroup -detailed".

For technical information, type: "get-help Repair-AppvClientConnectionGroup -full".

For online help, type: "get-help Repair-AppvClientConnectionGroup -online"