



Windows PowerShell Get-Help on Cmdlet 'Restart-AzSignalR'

PS:\>Get-HELP Restart-AzSignalR -Full

NAME

Restart-AzSignalR

SYNOPSIS

Restart a SignalR service.

SYNTAX

Restart-AzSignalR [-AsJob] [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] -InputObject

<Microsoft.Azure.Commands.SignalR.Models.PSSignalRResource> [-PassThru] [-Confirm] [-WhatIf]

[<CommonParameters>]

Restart-AzSignalR [-Name] <System.String> [-AsJob] [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]

[-PassThru] [-ResourceGroupName <System.String>] [-Confirm] [-WhatIf] [<CommonParameters>]

Restart-AzSignalR [-AsJob] [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-PassThru]

-ResourceId

<System.String> [-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

Restart a SignalR service.

PARAMETERS

-AsJob <System.Management.Automation.SwitchParameter>

Run the cmdlet in background job.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.SignalR.Models.PSSignalRResource>

The SignalR resource object.

Required? true

Position? named

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-Name <System.String>

The SignalR service name.

Required? true

Position? 0

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-PassThru <System.Management.Automation.SwitchParameter>

{{ Fill PassThru Description }}

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-ResourceGroupName <System.String>

The resource group name. The default one will be used if not specified.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-ResourceId <System.String>

The SignalR service resource ID.

Required? true

Position? named
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet is not run.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

System.String

OUTPUTS

System.Boolean

NOTES

----- Restart a specific SignalR service -----

Restart-AzSignalR -ResourceGroupName myResourceGroup -Name mysignalr1 -PassThru

True

The default resource group can be set by `Set-AzDefault -ResourceGroupName myResourceGroup`.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.signalr/restart-azsignalr>