



Full credit is given to all the above companies including the Operating System that this PDF file was generated!

Windows PowerShell Get-Help on Cmdlet 'Restart-AzWebApp'

PS:\>Get-HELP Restart-AzWebApp -Full

NAME

Restart-AzWebApp

SYNOPSIS

Restarts an Azure Web App.

SYNTAX

```
Restart-AzWebApp [-ResourceGroupName] <System.String> [-Name] <System.String> [-DefaultProfile  
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-SoftRestart]  
[<CommonParameters>]
```

```
Restart-AzWebApp [-WebApp] <Microsoft.Azure.Commands.WebApps.Models.PSSite> [-DefaultProfile  
<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-SoftRestart]  
[<CommonParameters>]
```

DESCRIPTION

The Restart-AzWebApp cmdlet stops and then starts an Azure Web App. If the Web App is in a stopped state, use the Start-AzWebApp cmdlet.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

WebApp Name

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ResourceGroupName <System.String>

Resource Group Name

Required? true

Position? 0

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-SoftRestart <System.Management.Automation.SwitchParameter>

Specify true to apply the configuration settings and restarts the app only if necessary. By default, the API always restarts and reprovisions the app.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WebApp <Microsoft.Azure.Commands.WebApps.Models.PSSite>

WebApp Object

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByValue)
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkId=113216>).

INPUTS

System.String

Microsoft.Azure.Commands.WebApps.Models.PSSite

OUTPUTS

Microsoft.Azure.Commands.WebApps.Models.PSSite

NOTES

----- Example 1: Restart a Web App -----

```
Restart-AzWebApp -ResourceGroupName "Default-Web-WestUS" -Name "ContosoSite"
```

This command stops the Azure Web App named ContosoSite that belongs to the resource group named Default-Web-WestUS and then restarts it.

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.websites/restart-azwebapp>

[Get-AzWebApp](#)

[New-AzWebApp](#)

[Remove-AzWebApp](#)

[Start-AzWebApp](#)

[Stop-AzWebApp](#)