



Windows PowerShell Get-Help on Cmdlet 'Restart-AzWebAppSlot'

PS:\>Get-HELP Restart-AzWebAppSlot -Full

NAME

Restart-AzWebAppSlot

SYNOPSIS

Restarts an Azure Web App Slot.

SYNTAX

```
Restart-AzWebAppSlot [-ResourceGroupName] <System.String> [-Name] <System.String> [-Slot] <System.String>
[-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-SoftRestart]
[<CommonParameters>]
```

```
Restart-AzWebAppSlot [-WebApp] <Microsoft.Azure.Commands.WebApps.Models.PSSite> [-DefaultProfile
    <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-SoftRestart]
[<CommonParameters>]
```

DESCRIPTION

The Restart-AzWebAppSlot cmdlet stops and then starts an Azure Web App Slot. If the Web App Slot is in a stopped

state, use the Start-AzWebAppSlot cmdlet.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Name <System.String>

WebApp Name

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ResourceGroupName <System.String>

Resource Group Name

Required? true

Position? 0

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-Slot <System.String>

WebApp Slot Name

Required?	true
Position?	2
Default value	None
Accept pipeline input?	False
Accept wildcard characters?	false

-SoftRestart <System.Management.Automation.SwitchParameter>

Specify true to apply the configuration settings and restarts the app only if necessary. By default, the API always restarts and reprovisions the app.

Required?	false
Position?	named
Default value	False
Accept pipeline input?	False
Accept wildcard characters?	false

-WebApp <Microsoft.Azure.Commands.WebApps.Models.PSSite>

WebApp Object

Required?	true
Position?	0
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

System.String

Microsoft.Azure.Commands.WebApps.Models.PSSite

OUTPUTS

Microsoft.Azure.Commands.WebApps.Models.PSSite

NOTES

----- Example 1 -----

Restart-AzWebAppSlot -ResourceGroupName "Default-Web-WestUS" -Name "ContosoWebApp" -Slot "Slot001"

This command restarts the slot Slot001 for the web app ContosoWebApp associated with the resource group Default-Web-WestUS

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.websites/restart-azwebappslot>

Get-AzWebAppSlot

New-AzWebAppSlot

Remove-AzWebAppSlot

Set-AzWebAppSlot

Start-AzWebAppSlot

Stop-AzWebAppSlot

Get-AzWebApp