



Windows PowerShell Get-Help on Cmdlet 'Restore-AzWebAppBackup'

PS:\>Get-HELP Restore-AzWebAppBackup -Full

NAME

Restore-AzWebAppBackup

SYNOPSIS

Restores an Azure Web App Backup.

SYNTAX

```
Restore-AzWebAppBackup [-ResourceGroupName] <System.String> [-Name] <System.String> [[-Slot] <System.String>]
[-StorageAccountUrl] <System.String> [-BlobName]
                        <System.String> [-AppServicePlan <System.String>] [-Databases
<Microsoft.Azure.Management.WebSites.Models.DatabaseBackupSetting[]>] [-DefaultProfile
                        <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
[-IgnoreConflictingHostNames] [-Overwrite] [<CommonParameters>]
```

```
Restore-AzWebAppBackup [-WebApp] <Microsoft.Azure.Commands.WebApps.Models.PSSite> [-StorageAccountUrl]
<System.String> [-BlobName] <System.String> [-AppServicePlan
                        <System.String>] [-Databases <Microsoft.Azure.Management.WebSites.Models.DatabaseBackupSetting[]>]
[-DefaultProfile
                        <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>]
```

`[-IgnoreConflictingHostNames] [-Overwrite] [<CommonParameters>]`

DESCRIPTION

The `Restore-AzWebAppBackup` cmdlet restores an Azure Web App Backup.

PARAMETERS

`-AppServicePlan <System.String>`

The name of the App Service Plan for the restored app. If left empty, the app's current App Service Plan is used.

Required? false

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

`-BlobName <System.String>`

Blob Name

Required? true

Position? 4

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

`-Databases <Microsoft.Azure.Management.WebSites.Models.DatabaseBackupSetting[]>`

Databases of type `DatabaseBackupSetting[]`

Required? false

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-IgnoreConflictingHostNames <System.Management.Automation.SwitchParameter>

Ignore Conflicting HostNames Option

Required? false

Position? named

Default value False

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Name <System.String>

WebApp Name

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-Overwrite <System.Management.Automation.SwitchParameter>

Overwrite Option

Required? false

Position? named
Default value False
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-ResourceGroupName <System.String>

Resource Group Name

Required? true
Position? 0
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-Slot <System.String>

WebApp Slot Name

Required? false
Position? 2
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-StorageAccountUrl <System.String>

Storage Account Url

Required? true
Position? 3
Default value None
Accept pipeline input? True (ByPropertyName)
Accept wildcard characters? false

-WebApp <Microsoft.Azure.Commands.WebApps.Models.PSSite>

WebApp Object

Required?	true
Position?	0
Default value	None
Accept pipeline input?	True (ByValue)
Accept wildcard characters?	false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

System.String

Microsoft.Azure.Management.WebSites.Models.DatabaseBackupSetting[]

System.Management.Automation.SwitchParameter

Microsoft.Azure.Commands.WebApps.Models.PSSite

OUTPUTS

System.Void

NOTES

----- Example 1 -----

```
Restore-AzWebAppBackup -ResourceGroupName "Default-Web-WestUS" -Name "ContosoWebApp"  
-StorageAccountUrl "https://storageaccount.file.core.windows.net" -BlobName  
"myBlob"
```

Restores a backup of the specified app ContosoWebApp that is within resource group Default-Web-WestUS in blob "myBlob" located at
`https://storageaccount.file.core.windows.net`

----- Example 2 -----

```
Restore-AzWebAppBackup -BlobName 'myBlob' -Name 'ContosoWebApp' -Overwrite -ResourceGroupName  
'Default-Web-WestUS' -StorageAccountUrl  
'https://storageaccount.file.core.windows.net'
```

RELATED LINKS

Online Version: <https://learn.microsoft.com/powershell/module/az.websites/restore-azwebappbackup>