



Windows PowerShell Get-Help on Cmdlet 'Resume-AzMigrateServerReplication'

PS:\>Get-HELP Resume-AzMigrateServerReplication -Full

NAME

Resume-AzMigrateServerReplication

SYNOPSIS

Starts the replication that has been suspended.

SYNTAX

```
Resume-AzMigrateServerReplication -TargetObjectId <String> [-DeleteMigratedResource] [-SubscriptionId <String>]
[-DefaultProfile <PSObject>] [-Force] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Resume-AzMigrateServerReplication [-DeleteMigratedResource] [-SubscriptionId <String>] -InputObject <IMigrationItem>
[-DefaultProfile <PSObject>] [-Force] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials]
[-WhatIf] [-Confirm] [<CommonParameters>]
```

DESCRIPTION

The Resume-AzMigrateServerReplication starts the replication that has been suspended.

PARAMETERS

-TargetObjectID <String>

Specifies the replicating server for which the resume replication needs to be initiated.

The ID should be retrieved using the Get-AzMigrateServerReplication cmdlet.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-DeleteMigratedResource [<SwitchParameter>]

Specifies whether the migrated resources needs to be deleted.

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

Azure Subscription ID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-InputObject <IMigrationItem>`

Specifies the replicating server for which the resume replication needs to be initiated.

The server object can be retrieved using the `Get-AzMigrateServerReplication` cmdlet

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-DefaultProfile <PSObject>`

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

`-Force [<SwitchParameter>]`

Specifies whether the migrated resources needs to be deleted by Force.

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

`-Break [<SwitchParameter>]`

Wait for .NET debugger to attach

Required? false
Position? named
Default value False
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-Proxy <Uri>

The URI for the proxy server to use

Required? false
Position? named
Default value
Accept pipeline input? false
Accept wildcard characters? false

-ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

INPUTS

OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Migrate.Models.Api202301.IJob

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about_Hash_Tables.

INPUTOBJECT <IMigrationItem>: Specifies the replicating server for which the resume replication needs to be initiated. The server object can be retrieved using

the Get-AzMigrateServerReplication cmdlet

[Location <String>]: Resource Location

[ProviderSpecificDetail <IMigrationProviderSpecificSettings>]: The migration provider custom settings.

InstanceType <String>: Gets the instance type.

----- EXAMPLE 1 -----

PS C:\> Resume-AzMigrateServerReplication -TargetObjectID

"/Subscriptions/xxx-xxx-xxxxxx-xxx-xxx/resourceGroups/cbtsignoff2201rg/providers/Microsoft.RecoveryServices/va

ults/signoffccyapp3352vault/replicationFabrics/signoffccyappae52replicationfabric/replicationProtectionContainers/signoffccy
appae52replicationcontainer/replicationMigr

ationItems/idclab-vcen67-fareast-corp-micr-0f144e99-ba36-4649-b92b-8b06854aa539_5015f6d8-fc84-afdf-de47-1eab7933
0f00"

----- EXAMPLE 2 -----

```
PS C:\>$obj = Get-AzMigrateServerReplication -ProjectName "signoffccyproj" -ResourceGroupName "cbtsignoff2201rg"  
-MachineName "Win2k16"
```

```
Resume-AzMigrateServerReplication -InputObject $obj
```

RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.migrate/resume-azmigrateserverreplication>