



Windows PowerShell Get-Help on Cmdlet 'Save-AzResourceGroupDeploymentStackTemplate'

PS:\>Get-HELP Save-AzResourceGroupDeploymentStackTemplate -Full

NAME

Save-AzResourceGroupDeploymentStackTemplate

SYNOPSIS

Saves a Resource Group scoped Deployment Stack Template.

SYNTAX

Save-AzResourceGroupDeploymentStackTemplate [-InputObject]

<Microsoft.Azure.Commands.ResourceManager.Cmdlets.SdkModels.PSDeploymentStack> [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Pre]

[<CommonParameters>]

Save-AzResourceGroupDeploymentStackTemplate [-ResourceGroupName] <System.String> [-StackName]

<System.String> [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Pre]

[<CommonParameters>]

Save-AzResourceGroupDeploymentStackTemplate [-DefaultProfile

<Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>] [-Pre]

-ResourceId <System.String> [<CommonParameters>]

DESCRIPTION

Saves a template (or template link) for a resource group scoped deployment stack.

PARAMETERS

-DefaultProfile <Microsoft.Azure.Commands.Common.Authentication.Abstractions.Core.IAzureContextContainer>

The credentials, account, tenant, and subscription used for communication with Azure.

Required? false

Position? named

Default value None

Accept pipeline input? False

Accept wildcard characters? false

-InputObject <Microsoft.Azure.Commands.ResourceManager.Cmdlets.SdkModels.PSDeploymentStack>

The stack PS object

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByValue)

Accept wildcard characters? false

-Pre <System.Management.Automation.SwitchParameter>

When set, indicates that the cmdlet should use pre-release API versions when automatically determining which version to use.

Required? false

Position? named

Default value False

Accept pipeline input? False

Accept wildcard characters? false

-ResourceGroupName <System.String>

The name of the ResourceGroup where the DeploymentStack is deployed

Required? true

Position? 0

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-ResourceId <System.String>

ResourceId of the DeploymentStack to get

Required? true

Position? named

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

-StackName <System.String>

The name of the DeploymentStack to get

Required? true

Position? 1

Default value None

Accept pipeline input? True (ByPropertyName)

Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,

ErrorAction, ErrorVariable, WarningAction, WarningVariable,

OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters](https://go.microsoft.com/fwlink/?LinkID=113216) (https://go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

System.String

OUTPUTS

Microsoft.Azure.Commands.ResourceManager.Cmdlets.SdkModels.PSDeploymentStackTemplateDefinition

NOTES

Example 1: Saves the template used for the deployment stack MyRGStack in the resource group MyResourceGroup

```
Save-AzResourceGroupDeploymentStackTemplate -ResourceGroupName MyResourceGroup -StackName MyRGStack
```

Save a template from a stack named 'MyRGStack' under an RG named 'MyResourceGroup'.

RELATED LINKS

Online

Version:

<https://learn.microsoft.com/powershell/module/az.resources/Save-AzResourceGroupDeploymentStackTemplate>