



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Set-AppvPublishingServer'

PS C:\Users\wahid> Get-Help Set-AppvPublishingServer

NAME

Set-AppvPublishingServer

SYNOPSIS

Modifies properties of an App-V Publishing Server.

SYNTAX

Set-AppvPublishingServer [-Server] <AppvPublishingServer>

[[[-GlobalRefreshEnabled] <Boolean>] [[-GlobalRefreshOnLogon] <Boolean>]

[[[-GlobalRefreshInterval] <UInt32>] [[-GlobalRefreshIntervalUnit] {Hour |

Day}] [[-UserRefreshEnabled] <Boolean>] [[-UserRefreshOnLogon] <Boolean>]

[[[-UserRefreshInterval] <UInt32>] [[-UserRefreshIntervalUnit] {Hour | Day}]

[<CommonParameters>]

Set-AppvPublishingServer [-ServerId] <UInt32> [[[-GlobalRefreshEnabled]

<Boolean>] [[[-GlobalRefreshOnLogon] <Boolean>] [[-GlobalRefreshInterval]

<UInt32>] [[[-GlobalRefreshIntervalUnit] {Hour | Day}] [[-UserRefreshEnabled]

<Boolean>] [[[-UserRefreshOnLogon] <Boolean>] [[-UserRefreshInterval] <UInt32>]

[[[-UserRefreshIntervalUnit] {Hour | Day}] [<CommonParameters>]

DESCRIPTION

The Set-AppvPublishingServer cmdlet modifies properties of an already existing Microsoft Application Virtualization (App-V) Publishing Server. To obtain an App-V Publishing Server object, use the Get-AppvPublishingServer cmdlet.

PARAMETERS

-GlobalRefreshEnabled <Boolean>

Specifies whether the server does automatic syncs with the publishing server for all globally published packages.

-GlobalRefreshInterval <UInt32>

Specifies a time span that represents the period where refreshes occur for packages published globally.

-GlobalRefreshIntervalUnit <IntervalUnit>

Specifies the unit of time measurement. The acceptable values for this parameter are: day and hour.

-GlobalRefreshOnLogon <Boolean>

Specifies whether a refresh occurs for all package published globally every time that a user logs into the target computer.

-Server <AppvPublishingServer>

Specifies an AppvPublishingServer object. To obtain an AppvPublishingServer object, use the Get-AppvPublishingServer cmdlet.

-ServerId <UInt32>

Specifies the identifier for the App-V Publishing Server. This can be queried using the Get-AppvPublishingServer cmdlet.

-UserRefreshEnabled <Boolean>

Specifies whether user refresh is enabled.

-UserRefreshInterval <UInt32>

Specifies the identifier for the App-V Publishing Server. This can be queried using the Get-AppvPublishingServer cmdlet.

-UserRefreshIntervalUnit <IntervalUnit>

Specifies the unit of time measurement. The acceptable values for this parameter are: day and hour.

-UserRefreshOnLogon <Boolean>

Specifies whether a refresh occurs every time that a user logs into the computer.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

REMARKS

To see the examples, type: "get-help Set-AppvPublishingServer -examples".

For more information, type: "get-help Set-AppvPublishingServer -detailed".

For technical information, type: "get-help Set-AppvPublishingServer -full".

For online help, type: "get-help Set-AppvPublishingServer -online"