



Full credit is given to all the above companies including the Operating System that this PDF file was generated!

Windows PowerShell Get-Help on Cmdlet 'Set-AppxDefaultVolume'

PS:\>Get-HELP Set-AppxDefaultVolume -Full

NAME

Set-AppxDefaultVolume

SYNOPSIS

Specifies a default appx volume.

SYNTAX

Set-AppxDefaultVolume [-Volume] <AppxVolume> [-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The `Set-AppxDefaultVolume` cmdlet specifies a default AppxVolume . The default AppxVolume is the default target for all deployment operations on the computer.

Deployment operations can specify a different non-default target volume.

PARAMETERS

-Volume <AppxVolume>

Specifies the path a volume. This cmdlet sets the volume that this parameter specifies to be the default Deployment

target for the computer.

Required? true
Position? 1
Default value None
Accept pipeline input? True (ByPropertyName, ByValue)
Accept wildcard characters? false

-Confirm <System.Management.Automation.SwitchParameter>

Prompts you for confirmation before running the cmdlet.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

-WhatIf <System.Management.Automation.SwitchParameter>

Shows what would happen if the cmdlet runs. The cmdlet isn't run.

Required? false
Position? named
Default value False
Accept pipeline input? False
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about_CommonParameters (<https://go.microsoft.com/fwlink/?LinkID=113216>).

OUTPUTS

NOTES

----- Example 1: Set a default volume by using a path -----

```
Set-AppxDefaultVolume -Volume F:\
```

This command sets the default volume to be the volume `F:`.

----- Example 2: Set a default volume by using an ID -----

```
Set-AppxDefaultVolume -Volume {ef23c8d6-b13c-4c4c-ae3b-7d5a162de9b9}
```

This command sets the default volume to be the one that has the specified media ID.

RELATED LINKS

Online

Version:

https://learn.microsoft.com/powershell/module/appx/set-appxdefaultvolume?view=windowsserver2022-ps&wt.mc_id=ps-get-help

[Get-AppxDefaultVolume](#)